

View Online at https://aerobasegroup.com/nsn/5910-01-584-7820

Chip type Reliability Indicator: Estabilished Reliability Failure Rate Level In Percent: 0.010 Body Length: 0.055 inches Body Width: 0.055 inches Body Width: 0.055 inches Body Height: Between 0.020 inches and 0.057 inches Schematic Diagram Designator: No common or grounded electrode (s) Section Quantity: 1 Capacitance Value Per Section: 2.700 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 150.0 dc single section Tolerance Range Per Section: -0.10/+0.10 picofarads single section Tolerance Range Per Section: -0.10/+0.10 picofarads single section Nonderated Continuous Voltage Rating And Type Per Section: -0.10/+0.10 picofarads single section Nonderated Continuous Voltage Rating And Type Per Section: -0.10/+0.10 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure:	Body Style:
Established Reliability Failure Rate Level In Percent: 0.010 Body Length: 0.055 inches Body Width: 0.055 inches Body Width: 0.055 inches Body Height: 0.055 inches Body Height: Between 0.020 inches and 0.057 inches Schematic Diagram Designator: No common or grounded electrode (s) Section Quantity: 1 Capacitance Value Per Section: 2.700 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Scion Guantity: 1 So.0 dc single section Ciolo/+0.10 picofarads single section C	Chip type
Reliability Failure Rate Level In Percent:0.010Body Length:0.055 inchesBody Width:0.055 inchesBody Height:Between 0.020 inches and 0.057 inchesSchematic Diagram Designator:No common or grounded electrode (s)Section Quantity:1Capacitance Value Per Section:2.700 picofarads single sectionNonderated Operating Temp:Between -55.0 degrees celsius and 125.0 degrees celsiusNonderated Continuous Voltage Rating And Type Per Section:150.0 dc single sectionTolerance Range Per Section:-0.10/+0.10 picofarads single sectionToloring Type And Quantity:2 bonding padShelf Life:N/a	Reliability Indicator:
0.010 Body Length: 0.055 inches Body Width: 0.055 inches Body Height: Between 0.020 inches and 0.057 inches Schematic Diagram Designator: No common or grounded electrode (s) Section Quantity: 1 Capacitance Value Per Section: 2.700 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 150.0 dc single section Colerance Range Per Section: -0.10/+0.10 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a	Established
Body Length:0.055 inchesBody Width:0.055 inchesBody Height:Between 0.020 inches and 0.057 inchesSchematic Diagram Designator:No common or grounded electrode (s)Section Quantity:1Capacitance Value Per Section:2.700 picofarads single sectionNonderated Operating Temp:Between -55.0 degrees celsius and 125.0 degrees celsiusNonderated Continuous Voltage Rating And Type Per Section:150.0 dc single sectionTolerance Range Per Section:-0.10/+0.10 picofarads single sectionTolerance Range Per Section:-0.10/+0.10 picofarads single sectionShelf Life:N/a	Reliability Failure Rate Level In Percent:
0.055 inches Body Width: 0.055 inches Body Height: Between 0.020 inches and 0.057 inches Schematic Diagram Designator: No common or grounded electrode (s) Section Quantity: 1 Capacitance Value Per Section: 2.700 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 150.0 dc single section Tolerance Range Per Section: -0.10/+0.10 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a	0.010
Body Width:0.055 inchesBody Height:Between 0.020 inches and 0.057 inchesSchematic Diagram Designator:No common or grounded electrode (s)Section Quantity:1Capacitance Value Per Section:2.700 picofarads single sectionNonderated Operating Temp:Between -55.0 degrees celsius and 125.0 degrees celsiusNonderated Continuous Voltage Rating And Type Per Section:150.0 dc single sectionTolerance Range Per Section:-0.10/+0.10 picofarads single sectionTerminal Type And Quantity:2 bonding padShelf Life:N/a	Body Length:
0.055 inches Body Height: Between 0.020 inches and 0.057 inches Schematic Diagram Designator: No common or grounded electrode (s) Section Quantity: 1 Capacitance Value Per Section: 2.700 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 150.0 dc single section Tolerance Range Per Section: -0.10/+0.10 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a	0.055 inches
Body Height: Between 0.020 inches and 0.057 inches Schematic Diagram Designator: No common or grounded electrode (s) Section Quantity: 1 Capacitance Value Per Section: 2.700 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 150.0 dc single section -0.10/+0.10 picofarads single section -0.10/+0.10 picofarads single section Section Range Per Section: -0.10/+0.10 picofarads single section Section Range Per Section: -0.10/+0.10 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a	Body Width:
Between 0.020 inches and 0.057 inches Schematic Diagram Designator: No common or grounded electrode (s) Section Quantity: 1 Capacitance Value Per Section: 2.700 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 150.0 dc single section Tolerance Range Per Section: -0.10/+0.10 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a	0.055 inches
Schematic Diagram Designator: No common or grounded electrode (s) Section Quantity: 1 Capacitance Value Per Section: 2.700 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 150.0 dc single section Tolerance Range Per Section: -0.10/+0.10 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a	Body Height:
No common or grounded electrode (s) Section Quantity: 1 Capacitance Value Per Section: 2.700 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 150.0 dc single section Tolerance Range Per Section: -0.10/+0.10 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a	Between 0.020 inches and 0.057 inches
Section Quantity: 1 Capacitance Value Per Section: 2.700 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 150.0 dc single section Tolerance Range Per Section: -0.10/+0.10 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a	Schematic Diagram Designator:
1 Capacitance Value Per Section: 2.700 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 150.0 dc single section Tolerance Range Per Section: -0.10/+0.10 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a	No common or grounded electrode (s)
Capacitance Value Per Section: 2.700 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 150.0 dc single section Tolerance Range Per Section: -0.10/+0.10 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a	Section Quantity:
2.700 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 150.0 dc single section Tolerance Range Per Section: -0.10/+0.10 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a	1
Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 150.0 dc single section Tolerance Range Per Section: -0.10/+0.10 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a	Capacitance Value Per Section:
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 150.0 dc single section Tolerance Range Per Section: -0.10/+0.10 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a	2.700 picofarads single section
Nonderated Continuous Voltage Rating And Type Per Section: 150.0 dc single section Tolerance Range Per Section: -0.10/+0.10 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a	Nonderated Operating Temp:
150.0 dc single section Tolerance Range Per Section: -0.10/+0.10 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a	Between -55.0 degrees celsius and 125.0 degrees celsius
Tolerance Range Per Section: -0.10/+0.10 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a	Nonderated Continuous Voltage Rating And Type Per Section:
-0.10/+0.10 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a	150.0 dc single section
Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a	Tolerance Range Per Section:
2 bonding pad Shelf Life: N/a	-0.10/+0.10 picofarads single section
Shelf Life: N/a	Terminal Type And Quantity:
N/a	2 bonding pad
	Shelf Life:
Unit Of Measure:	N/a
	Unit Of Measure:
	-
Demilitarization:	Demilitarization:
No	No
	Fiig:
Fiig:	A010b0
Fiig:	-
-	