

View Online at https://aerobasegroup.com/nsn/5910-01-590-5394

Body Style: Chip type Reliability Indicator: Not established Body Length: Between 1.450 inches and 1.750 inches Body Width: Between 0.650 inches and 0.950 inches Body Height: 0.8 millimeters Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 1000000.000 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 16.0 dc single section 7olerance Range Per Section: -0.50/+0.50 picofarads single section Product Name: Ceramic chip capacitor Special Features: Ceramic capacitor; 16.0 dc jing capacitor Special Features: Ceramic capacitor; Special Features: Ceramic capacitor; Special Features: Ceramic capacitor; Special Features: Ceramic capacitor; Special Features: Ceramic capacitor; <
Reliability Indicator: Not established Body Length: Between 1.450 inches and 1.750 inches Body Width: Between 0.650 inches and 0.950 inches Body Height: 0.8 millimeters Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 100000.000 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 16.0 dc single section 7.01/20.050 picofarads single section Polyticol for and single section Costrolinous Voltage Rating And Type Per Section: 16.0 dc single section 7.050/+0.50 picofarads single section Product Name: Ceramic chip capacitor Special Features: Ceramic capacitor; 16 volt; 0603 chp size; x7r temperature characteristics; end metalization; tin plated, nickel barrier
Not established Body Length: Between 1.450 inches and 1.750 inches Body Width: Between 0.650 inches and 0.950 inches Body Height: 0.8 millimeters Schematic Diagram Designator: Not common or grounded electrode (s) Capacitance Value Per Section: 100000.000 picofarads single section Monderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Monderated Continuous Voltage Rating And Type Per Section: 16.0 dc single section Polerance Range Per Section: -0.50/+0.50 picofarads single section Porduct Name: Ceramic chip capacitor Geramic chip capacitor Schip (Stop (Stop) (Stop) size; x7r temperature characteristics; end metalization: tin plated, nickel barrier
Body Length: Between 1.450 inches and 1.750 inches Body Width: Between 0.650 inches and 0.950 inches Body Height: 0.8 millimeters Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 1000000.000 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 10.000/0.050 picofarads single section Poly-0.50 picofarads single section Product Name: Ceramic chip capacitor Geramic chip capacitor; 16 volt; 0603 chp size; x7r temperature characteristics; end metalization: tin plated, nickel barrier
Between 1.450 inches and 1.750 inches Body Width: Between 0.650 inches and 0.950 inches Body Height: 0.8 millimeters Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 1000000.000 picofarads single section Monderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 16.0 dc single section Poly-to.50 picofarads single section Product Name: Ceramic chip capacitor Special Features: Ceramic capacitor; 16 volt; 0603 chp size; x7r temperature characteristics; end metalization: tin plated, nickel barrier
Body Width:Between 0.650 inches and 0.950 inchesBody Height:0.8 millimetersSchematic Diagram Designator:No common or grounded electrode (s)Capacitance Value Per Section:100000.000 picofarads single sectionNonderated Operating Temp:Between -55.0 degrees celsius and 85.0 degrees celsiusNonderated Continuous Voltage Rating And Type Per Section:16.0 dc single section10.050/+0.50 picofarads single sectionProduct Name:Ceramic chip capacitorSection Froduct Name:Ceramic chip capacitorForduct Name:Ceramic chip capacitor; 16 volt; 0603 chp size; x7r temperature characteristics; end metalization: tin plated, nickel barrierFerminal Type And Quantity:
Between 0.650 inches and 0.950 inches Body Height: 0.8 millimeters Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 1000000.000 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 16.0 dc single section Poly-1.50 picofarads single section Product Name: Ceramic chip capacitor Special Features: Ceramic capacitor; 16 volt; 0603 chp size; x7r temperature characteristics; end metalization: tin plated, nickel barrier Terminal Type And Quantity:
Body Height: 0.8 millimeters Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 100000.000 picofarads single section Monderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 16.0 dc single section 70.50/+0.50 picofarads single section Product Name: Ceramic chip capacitor Special Features: Ceramic capacitor; 16 volt; 0603 chp size; x7r temperature characteristics; end metalization: tin plated, nickel barrier
0.8 millimeters Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 1000000.000 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 16.0 dc single section 16.0 dc single section 16.0 dc single section 16.0 dc single section Colerance Range Per Section: -0.50/+0.50 picofarads single section Product Name: Ceramic chip capacitor Special Features: Ceramic capacitor; 16 volt; 0603 chp size; x7r temperature characteristics; end metalization: tin plated, nickel barrier Terminal Type And Quantity:
Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 1000000.000 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 16.0 dc single section Tolerance Range Per Section: -0.50/+0.50 picofarads single section Product Name: Ceramic chip capacitor Special Features: Ceramic capacitor; 16 volt; 0603 chp size; x7r temperature characteristics; end metalization: tin plated, nickel barrier Terminal Type And Quantity:
No common or grounded electrode (s) Capacitance Value Per Section: 1000000.000 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 16.0 dc single section 16.0 dc single section Tolerance Range Per Section: -0.50/+0.50 picofarads single section Product Name: Ceramic chip capacitor Special Features: Ceramic capacitor; 16 volt; 0603 chp size; x7r temperature characteristics; end metalization: tin plated, nickel barrier Terminal Type And Quantity:
Capacitance Value Per Section:100000.000 picofarads single sectionNonderated Operating Temp:Between -55.0 degrees celsius and 85.0 degrees celsiusNonderated Continuous Voltage Rating And Type Per Section:16.0 dc single sectionTolerance Range Per Section:-0.50/+0.50 picofarads single sectionProduct Name:Ceramic chip capacitorSpecial Features:Ceramic capacitor; 16 volt; 0603 chp size; x7r temperature characteristics; end metalization: tin plated, nickel barrierTerminal Type And Quantity:
 100000.000 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 16.0 dc single section Tolerance Range Per Section: -0.50/+0.50 picofarads single section Product Name: Ceramic chip capacitor Special Features: Ceramic capacitor; 16 volt; 0603 chp size; x7r temperature characteristics; end metalization: tin plated, nickel barrier
Nonderated Operating Temp:Between -55.0 degrees celsius and 85.0 degrees celsiusNonderated Continuous Voltage Rating And Type Per Section:16.0 dc single sectionTolerance Range Per Section:-0.50/+0.50 picofarads single sectionProduct Name:Ceramic chip capacitorSpecial Features:Ceramic capacitor; 16 volt; 0603 chp size; x7r temperature characteristics; end metalization: tin plated, nickel barrierTerminal Type And Quantity:
 Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 16.0 dc single section Tolerance Range Per Section: -0.50/+0.50 picofarads single section Product Name: Ceramic chip capacitor Special Features: Ceramic capacitor; 16 volt; 0603 chp size; x7r temperature characteristics; end metalization: tin plated, nickel barrier Terminal Type And Quantity:
 Nonderated Continuous Voltage Rating And Type Per Section: 16.0 dc single section Tolerance Range Per Section: -0.50/+0.50 picofarads single section Product Name: Ceramic chip capacitor Special Features: Ceramic capacitor; 16 volt; 0603 chp size; x7r temperature characteristics; end metalization: tin plated, nickel barrier Terminal Type And Quantity:
 16.0 dc single section Tolerance Range Per Section: -0.50/+0.50 picofarads single section Product Name: Ceramic chip capacitor Special Features: Ceramic capacitor; 16 volt; 0603 chp size; x7r temperature characteristics; end metalization: tin plated, nickel barrier Terminal Type And Quantity:
Tolerance Range Per Section: -0.50/+0.50 picofarads single section Product Name: Ceramic chip capacitor Special Features: Ceramic capacitor; 16 volt; 0603 chp size; x7r temperature characteristics; end metalization: tin plated, nickel barrier Terminal Type And Quantity:
-0.50/+0.50 picofarads single section Product Name: Ceramic chip capacitor Special Features: Ceramic capacitor; 16 volt; 0603 chp size; x7r temperature characteristics; end metalization: tin plated, nickel barrier Terminal Type And Quantity:
Product Name: Ceramic chip capacitor Special Features: Ceramic capacitor; 16 volt; 0603 chp size; x7r temperature characteristics; end metalization: tin plated, nickel barrier Terminal Type And Quantity:
Ceramic chip capacitor Special Features: Ceramic capacitor; 16 volt; 0603 chp size; x7r temperature characteristics; end metalization: tin plated, nickel barrier Terminal Type And Quantity:
Special Features: Ceramic capacitor; 16 volt; 0603 chp size; x7r temperature characteristics; end metalization: tin plated, nickel barrier Terminal Type And Quantity:
Ceramic capacitor; 16 volt; 0603 chp size; x7r temperature characteristics; end metalization: tin plated, nickel barrier Terminal Type And Quantity:
Terminal Type And Quantity:
2 bonding pad
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A010b0