

View Online at https://aerobasegroup.com/nsn/5910-01-592-1203

Body Style: Chip type Reliability Indicator: Not established Body Length: 2.0 millimeters Body Width: 1.3 millimeters Body Height: 0.6 millimeters Chematic Diagram Designator: No common or grounded electrode (s) End Application: RADA-RS-ET,-5840 Capacitance Value Per Section: 10.000 nanofarads single section Monderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Special Features: Lea (pb) -free; rohs compliant Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Reliability Indicator: Not established Body Length: 2.0 millimeters Body Width: 1.3 millimeters Body Height: 0.6 millimeters Schematic Diagram Designator: No common or grounded electrode (s) End Application: RADA-RS-ET,-5840 Capacitance Value Per Section: 10.000 nanofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Solod c single section Special Features: Lea (pb) -free; rohs compliant Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Permiltarization:	Body Style:
Not established Body Length: 2.0 millimeters Body Width: 1.3 millimeters Body Height: 0.6 millimeters Schematic Diagram Designator: No common or grounded electrode (s) End Application: RADA-RS-ET,-5840 Capacitance Value Per Section: 10.000 nanofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Special Features: Lea (pb) -free; rohs compliant Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure:	Chip type
Body Length: 2.0 millimeters Body Width: 1.3 millimeters Body Height: 0.6 millimeters Schematic Diagram Designator: No common or grounded electrode (s) End Application: RADA-RS-ET,-5840 Capacitance Value Per Section: 10.000 nanofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Special Features: Lea (pb) -free; rohs compliant Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization:	Reliability Indicator:
2.0 millimeters Body Width: 1.3 millimeters Body Height: 0.6 millimeters Schematic Diagram Designator: No common or grounded electrode (s) End Application: RADA-RS-ET,-5840 Capacitance Value Per Section: 10.000 nanofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Special Features: Lea (pb) -free; rohs compliant Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization:	Not established
Body Width: 1.3 millimeters Body Height: 0.6 millimeters Schematic Diagram Designator: No common or grounded electrode (s) End Application: RADA-RS-ET,-5840 Capacitance Value Per Section: 10.000 nanofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Special Features: Lea (pb) -free; rohs compliant Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: 	Body Length:
1.3 millimeters Body Height: 0.6 millimeters Schematic Diagram Designator: No common or grounded electrode (s) End Application: RADA-RS-ET,-5840 Capacitance Value Per Section: 10.000 nanofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Special Features: Lea (pb) -free; rohs compliant Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization:	2.0 millimeters
Body Height: 0.6 millimeters Schematic Diagram Designator: No common or grounded electrode (s) End Application: RADA-RS-ET,-5840 Capacitance Value Per Section: 10.000 nanofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Special Features: Lea (pb) -free; rohs compliant Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization:	Body Width:
0.6 millimeters Schematic Diagram Designator: No common or grounded electrode (s) End Application: RADA-RS-ET,-5840 Capacitance Value Per Section: 10.000 nanofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Special Features: Lea (pb) -free; rohs compliant Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: 	1.3 millimeters
Schematic Diagram Designator: No common or grounded electrode (s) End Application: RADA-RS-ET,-5840 Capacitance Value Per Section: 10.000 nanofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Special Features: Lea (pb) -free; rohs compliant Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization:	Body Height:
No common or grounded electrode (s) End Application: RADA-RS-ET,-5840 Capacitance Value Per Section: 10.000 nanofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Special Features: Lea (pb) -free; rohs compliant Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: 	0.6 millimeters
End Application: RADA-RS-ET,-5840 Capacitance Value Per Section: 10.000 nanofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Special Features: Lea (pb) -free; rohs compliant Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: 	Schematic Diagram Designator:
RADA-RS-ET,-5840 Capacitance Value Per Section: 10.000 nanofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Special Features: Lea (pb) -free; rohs compliant Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: 	No common or grounded electrode (s)
Capacitance Value Per Section: 10.000 nanofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Special Features: Lea (pb) -free; rohs compliant Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization:	End Application:
10.000 nanofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Special Features: Lea (pb) -free; rohs compliant Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization:	RADA-RS-ET,-5840
Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Special Features: Lea (pb) -free; rohs compliant Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization:	Capacitance Value Per Section:
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Special Features: Lea (pb) -free; rohs compliant Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization:	10.000 nanofarads single section
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Special Features: Lea (pb) -free; rohs compliant Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization:	Nonderated Operating Temp:
50.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Special Features: Lea (pb) -free; rohs compliant Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization:	Between -55.0 degrees celsius and 125.0 degrees celsius
Tolerance Range Per Section: -5.00/+5.00 percent single section Special Features: Lea (pb) -free; rohs compliant Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization:	Nonderated Continuous Voltage Rating And Type Per Section:
-5.00/+5.00 percent single section Special Features: Lea (pb) -free; rohs compliant Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization:	50.0 dc single section
Special Features: Lea (pb) -free; rohs compliant Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization:	Tolerance Range Per Section:
Lea (pb) -free; rohs compliant Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization:	-5.00/+5.00 percent single section
Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization:	Special Features:
2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization:	Lea (pb) -free; rohs compliant
Shelf Life: N/a Unit Of Measure: Demilitarization:	Terminal Type And Quantity:
N/a Unit Of Measure: Demilitarization:	2 bonding pad
Unit Of Measure: Demilitarization:	Shelf Life:
	N/a
	Unit Of Measure:
No	Demilitarization:
	No
Fiig:	Fiig:
A010b0	A010b0