Electrolytic Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-595-4971

| - | |
|---|--|
| | Body Style: |
| | Chip type |
| | Reliability Indicator: |
| | Not established |
| | Body Length: |
| | 0.236 inches |
| | Body Width: |
| С | 0.126 inches |
| E | Body Height: |
| С | 0.102 inches |
| S | Schematic Diagram Designator: |
| | lo common or grounded electrode (s) |
| E | Electrical Polarization: |
| ٢ | lonpolarized |
| E | End Application: |
| E | 3-1 |
| C | Capacitance Value Per Section: |
| 1 | 0.000 microfarads single section |
| N | Ionderated Operating Temp: |
| | Between -55.0 degrees celsius and 125.0 degrees celsius |
| N | Ionderated Continuous Voltage Rating And Type Per Section: |
| 2 | 25.0 dc single section |
| T | olerance Range Per Section: |
| - | 10.00/+10.00 percent single section |
| C | Capacitive Electrode Material: |
| Т | antalum |
| S | Special Features: |
| Т | in lead terminations; 7 inch reel |
| T | erminal Type And Quantity: |
| 2 | bonding pad |
| S | Shelf Life: |
| ٨ | l/a |
| ι | Jnit Of Measure: |
| - | - |
| C | Demilitarization: |
| ٨ | lo |
| F | iig: |
| | \010b0 |