NSN 5910-01-606-3416

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-606-3416 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 0.001 **Terminal Length:** Between 1.250 inches and 1.750 inches **Body Diameter:** Between 0.274 inches and 0.305 inches **Body Length:** Between 0.655 inches and 0.717 inches **Terminal Diameter:** Between 0.023 inches and 0.027 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Electrical Polarization:** Polarized **Section Quantity: Capacitance Value Per Section:** 22.0 microfarads single section **Nonderated Operating Temp:** 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 23.0 dc single section **Tolerance Range Per Section:** -10.0 to 10.0 percent single section Case Material: Metal **Capacitive Electrode Material: Tantalum Product Name:** Solid-electrolyte tantalex capacitor **Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5910-01-606-3416

Electrolytic Fixed Capacitor - Page 2 of 2



Fiig:

A010b0