

View Online at <https://aerobasegroup.com/nsn/5910-01-611-4069>

Body Style:

Chip type

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

0.01

Body Length:

0.285 inches

Body Width:

0.150 inches

Body Height:

0.110 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Electrical Polarization:

Polarized

End Application:

Global hawk asip

Capacitance Value Per Section:

47.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

10.0 dc single section

Tolerance Range Per Section:

-10.00 to 10.00 percent single section

Case Material:

Ceramic

Capacitive Electrode Material:

Tantalum

Special Features:

Hot solder dipped (60 microinch min.)

Test Data Document:

81349-mil-prf-55365/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 bonding pad

Specification Data:

81349-mil-prf-55365 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0

Mil-std (military Standard):

Mil-prf-55365 spec.