

View Online at <https://aerobasegroup.com/nsn/5910-01-613-2899>

**Body Style:**

Chip type

**Reliability Indicator:**

Established

**Reliability Failure Rate Level In Percent:**

0.1

**Body Length:**

Between 0.164 inches and 0.188 inches

**Body Width:**

Between 0.238 inches and 0.262 inches

**Body Height:**

0.059 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**End Application:**

Nsn: 1440-01-393-6361, launcher, guided missile, aircraft

**Capacitance Value Per Section:**

220.0 nanofarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

50.0 dc single section

**Tolerance Range Per Section:**

-10.0 to 10.0 percent single section

**Product Name:**

Surface mount multilayer ceramic chip capacitors

**Test Data Document:**

81349-mil-prf-55681 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 bonding pad

**Specification Data:**

81349-mil-prf-55681/11 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A010b0

**Mil-std (military Standard):**

Mil-prf-55681 spec.