## NSN 5910-01-615-4227

Electrolytic Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-615-4227
Body Style:
Chip type
Reliability Indicator:
Not established
Body Length:
0.287 inches
Body Width:
0.169 inches
Body Height:
0.122 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Electrical Polarization:
Polarized
End Application:
5865-01-567-8646
Capacitance Value Per Section:
330.000 microfarads single section
Nonderated Operating Temp:
Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius
Between -55.0 degrees celsius and 85.0 degrees celsius
Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:
Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  6.3 dc single section
Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  6.3 dc single section  Tolerance Range Per Section:
Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 6.3 dc single section  Tolerance Range Per Section: -10.0 to 10.0 percent single section
Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 6.3 dc single section  Tolerance Range Per Section: -10.0 to 10.0 percent single section  Capacitive Electrode Material:
Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 6.3 dc single section  Tolerance Range Per Section: -10.0 to 10.0 percent single section  Capacitive Electrode Material:  Tantalum
Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 6.3 dc single section  Tolerance Range Per Section: -10.0 to 10.0 percent single section  Capacitive Electrode Material:  Tantalum  Product Name:
Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 6.3 dc single section  Tolerance Range Per Section: -10.0 to 10.0 percent single section  Capacitive Electrode Material:  Tantalum  Product Name:  Tantalum capacitor
Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 6.3 dc single section  Tolerance Range Per Section: -10.0 to 10.0 percent single section  Capacitive Electrode Material:  Tantalum  Product Name:  Tantalum capacitor  Terminal Type And Quantity:
Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 6.3 dc single section  Tolerance Range Per Section: -10.0 to 10.0 percent single section  Capacitive Electrode Material:  Tantalum  Product Name:  Tantalum capacitor  Terminal Type And Quantity: 2 bonding pad
Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 6.3 dc single section  Tolerance Range Per Section: -10.0 to 10.0 percent single section  Capacitive Electrode Material:  Tantalum  Product Name:  Tantalum capacitor  Terminal Type And Quantity: 2 bonding pad  Shelf Life:
Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 6.3 dc single section  Tolerance Range Per Section: -10.0 to 10.0 percent single section  Capacitive Electrode Material:  Tantalum  Product Name:  Tantalum capacitor  Terminal Type And Quantity: 2 bonding pad  Shelf Life:  N/a
Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 6.3 dc single section  Tolerance Range Per Section: -10.0 to 10.0 percent single section  Capacitive Electrode Material:  Tantalum  Product Name:  Tantalum capacitor  Terminal Type And Quantity: 2 bonding pad  Shelf Life:  N/a
Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 6.3 dc single section  Tolerance Range Per Section: -10.0 to 10.0 percent single section  Capacitive Electrode Material:  Tantalum  Product Name:  Tantalum capacitor  Terminal Type And Quantity: 2 bonding pad  Shelf Life:  N/a  Unit Of Measure:
Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 6.3 dc single section  Tolerance Range Per Section: -10.0 to 10.0 percent single section  Capacitive Electrode Material:  Tantalum  Product Name:  Tantalum capacitor  Terminal Type And Quantity: 2 bonding pad  Shelf Life:  N/a  Unit Of Measure:  Demilitarization: