

View Online at https://aerobasegroup.com/nsn/5910-01-615-6402

Body Style:
Chip type
Reliability Indicator:
Not established
Body Length:
0.39 inches
Body Width:
0.20 inches
Body Height:
0.21 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
End Application:
4920-01-495-9100
Capacitance Value Per Section:
0.1 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
16.0 dc single section
16.0 dc single section Tolerance Range Per Section:
Tolerance Range Per Section:
Tolerance Range Per Section: -10.0 to 10.0 percent single section
Tolerance Range Per Section: -10.0 to 10.0 percent single section Terminal Type And Quantity:
Tolerance Range Per Section: -10.0 to 10.0 percent single section Terminal Type And Quantity: 2 bonding pad
Tolerance Range Per Section: -10.0 to 10.0 percent single section Terminal Type And Quantity: 2 bonding pad Shelf Life:
Tolerance Range Per Section: -10.0 to 10.0 percent single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a
Tolerance Range Per Section: -10.0 to 10.0 percent single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a
Tolerance Range Per Section: -10.0 to 10.0 percent single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure:
Tolerance Range Per Section: -10.0 to 10.0 percent single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization:
Tolerance Range Per Section: -10.0 to 10.0 percent single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No