

View Online at https://aerobasegroup.com/nsn/5910-01-615-7059

Body Style:
Chip type
Reliability Indicator:
Not established
Body Length:
1.6 millimeters
Body Width:
0.8 millimeters
Body Height:
0.8 millimeters
Schematic Diagram Designator:
No common or grounded electrode (s)
End Application:
5865-01-567-8646
Capacitance Value Per Section:
680.0 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section:
Nonderated Continuous Voltage Rating And Type Per Section:
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section:
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.0 to 10.0 picofarads single section
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.0 to 10.0 picofarads single section Terminal Type And Quantity:
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.0 to 10.0 picofarads single section Terminal Type And Quantity: 2 bonding pad
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.0 to 10.0 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life:
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.0 to 10.0 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.0 to 10.0 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.0 to 10.0 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure:
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.0 to 10.0 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization:
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.0 to 10.0 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No