

View Online at <https://aerobasegroup.com/nsn/5910-01-624-0649>

**Body Style:**

Chip type

**Reliability Indicator:**

Not established

**Terminal Length:**

1.3 millimeters

**Body Length:**

7.3 millimeters

**Body Width:**

4.3 millimeters

**Body Height:**

2.8 millimeters

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Anode Type:**

Solid

**Electrical Polarization:**

Polarized

**End Application:**

B-1

**Section Quantity:**

1

**Capacitance Value Per Section:**

15.0 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

25.0 dc single section

**Tolerance Range Per Section:**

-10.0 to 10.0 percent single section

**Case Material:**

Plastic

**Capacitive Electrode Material:**

Tantalum

**Dissipation Factor At Reference Temperature In Percent:**

6.00

**Equivalent Series Resistance At Reference Temperature In Ohms:**

1.00

**Dc Leakage At Reference Temp:**

3.80 microamperes

**Terminal Surface Treatment:**

Solder

**Terminal Type And Quantity:**

2 bonding pad

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0