## NSN 5910-01-625-1574

Electrolytic Fixed Capacitor - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5910-01-625-1574



Body Style: Chip type Reliability Indicator: Not established Body Length: 0.287 inches Body Width: 0.169 inches Body Height: 0.110 inches Schematic Diagram Designator: No common or grounded electrode (s) Electrical Polarization: Polarized Capacitance Value Per Section: 470000.0 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.0 to 10.0 percent single section
Reliability Indicator: Not established Body Length: 0.287 inches Body Width: 0.169 inches Body Height: 0.110 inches Schematic Diagram Designator: No common or grounded electrode (s) Electrical Polarization: Polarized Capacitance Value Per Section: 4700000.0 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.0 to 10.0 percent single section
Not established  Body Length:  0.287 inches  Body Width:  0.169 inches  Body Height:  0.110 inches  Schematic Diagram Designator:  No common or grounded electrode (s)  Electrical Polarization:  Polarized  Capacitance Value Per Section:  4700000.0 picofarads single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  50.0 dc single section  Tolerance Range Per Section: -10.0 to 10.0 percent single section
Body Length:  0.287 inches  Body Width:  0.169 inches  Body Height:  0.110 inches  Schematic Diagram Designator:  No common or grounded electrode (s)  Electrical Polarization:  Polarized  Capacitance Value Per Section:  4700000.0 picofarads single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  50.0 dc single section  Tolerance Range Per Section: -10.0 to 10.0 percent single section
0.287 inches  Body Width: 0.169 inches  Body Height: 0.110 inches  Schematic Diagram Designator: No common or grounded electrode (s)  Electrical Polarization:  Polarized  Capacitance Value Per Section: 4700000.0 picofarads single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section  Tolerance Range Per Section: -10.0 to 10.0 percent single section
Body Width:  0.169 inches  Body Height:  0.110 inches  Schematic Diagram Designator:  No common or grounded electrode (s)  Electrical Polarization:  Polarized  Capacitance Value Per Section:  4700000.0 picofarads single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  50.0 dc single section  Tolerance Range Per Section:  -10.0 to 10.0 percent single section
0.169 inches  Body Height: 0.110 inches  Schematic Diagram Designator: No common or grounded electrode (s)  Electrical Polarization: Polarized  Capacitance Value Per Section: 4700000.0 picofarads single section  Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section  Tolerance Range Per Section: -10.0 to 10.0 percent single section
Body Height:  0.110 inches  Schematic Diagram Designator:  No common or grounded electrode (s)  Electrical Polarization:  Polarized  Capacitance Value Per Section:  4700000.0 picofarads single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  50.0 dc single section  Tolerance Range Per Section:  -10.0 to 10.0 percent single section
0.110 inches  Schematic Diagram Designator:  No common or grounded electrode (s)  Electrical Polarization:  Polarized  Capacitance Value Per Section:  4700000.0 picofarads single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  50.0 dc single section  Tolerance Range Per Section: -10.0 to 10.0 percent single section
Schematic Diagram Designator:  No common or grounded electrode (s)  Electrical Polarization:  Polarized  Capacitance Value Per Section:  4700000.0 picofarads single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  50.0 dc single section  Tolerance Range Per Section:  -10.0 to 10.0 percent single section
No common or grounded electrode (s)  Electrical Polarization:  Polarized  Capacitance Value Per Section:  4700000.0 picofarads single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  50.0 dc single section  Tolerance Range Per Section:  -10.0 to 10.0 percent single section
Electrical Polarization:  Polarized  Capacitance Value Per Section:  4700000.0 picofarads single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  50.0 dc single section  Tolerance Range Per Section:  -10.0 to 10.0 percent single section
Polarized  Capacitance Value Per Section:  4700000.0 picofarads single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  50.0 dc single section  Tolerance Range Per Section:  -10.0 to 10.0 percent single section
Capacitance Value Per Section: 4700000.0 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.0 to 10.0 percent single section
4700000.0 picofarads single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  50.0 dc single section  Tolerance Range Per Section:  -10.0 to 10.0 percent single section
Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  50.0 dc single section  Tolerance Range Per Section:  -10.0 to 10.0 percent single section
Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  50.0 dc single section  Tolerance Range Per Section:  -10.0 to 10.0 percent single section
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section  Tolerance Range Per Section: -10.0 to 10.0 percent single section
50.0 dc single section  Tolerance Range Per Section: -10.0 to 10.0 percent single section
Tolerance Range Per Section: -10.0 to 10.0 percent single section
-10.0 to 10.0 percent single section
·
Capacitive Electrode Material:
Tantalum
Terminal Type And Quantity:
2 bonding pad
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: