Electrolytic Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-631-2545

| Body Style:  |  |
|--|--|
| Chip type  |  |
| Reliability Indicator:                                     |  |
| Not established  |  |
| Body Length:   |  |
| 3.5 millimeters  |  |
| Body Width:  |  |
| 2.8 millimeters  |  |
| Body Height:   |  |
| 1.9 millimeters  |  |
| Schematic Diagram Designator:                              |  |
| No common or grounded electrode (s)                        |  |
| Electrical Polarization:                                   |  |
| Polarized  |  |
| Section Quantity:  |  |
| 1  |  |
| Capacitance Value Per Section:                             |  |
| 33.0 microfarads single section                            |  |
| Nonderated Operating Temp:                                 |  |
| Between -55.0 degrees celsius and 105.0 degrees celsius    |  |
| Nonderated Continuous Voltage Rating And Type Per Section: |  |
| 6.3 dc single section                                      |  |
| Tolerance Range Per Section:                               |  |
| -20.0 to 20.0 percent single section                       |  |
| Capacitive Electrode Material:                             |  |
| Tantalum   |  |
| Terminal Type And Quantity:                                |  |
| 2 bonding pad  |  |
| Shelf Life:  |  |
| N/a  |  |
| Unit Of Measure:   |  |
|  |  |
| Demilitarization:  |  |
| No   |  |
| Fiig:  |  |
| A010b0   |  |
|  |  |
|  |  |