Electrolytic Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-633-9755

Body Style: Chip type Reliability Indicator: Not established Body Length: 7.3 millimeters Body Width: 4.3 millimeters Body Height: 4.1 millimeters Schematic Diagram Designator: No common or grounded electrode (s) Electrical Polarization: Non common or grounded electrode (s) Electrical Polarization: Nonpolarized End Application: B-1 Capacitance Value Per Section: 22.0 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Clerance Range Per Section: 10.0 to 10.0 percent single section Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 tab, solder lug Sheff Life: Na Unit Of Measure:  Demilitarization: No Fig: A010b0	Chiptype         Reliability Indicator:         Not established         Body Length:         7.3 millimeters         Body Width:         4.3 millimeters         Body Height:         4.1 millimeters         Schematic Diagram Designator:         No common or grounded electrode (s)         Electrical Polarization:         Nonpolarized         End Application:         8-1         Capacitance Value Per Section:         22.0 microfarads single section         Nonderated Operating Temp:         Between -55.0 degrees celsius and 85.0 degrees celsius         Nonderated Continuous Voltage Rating And Type Per Section:         35.0 dc single section         Tolerance Range Per Section:         -10.0 to 10.0 percent single section         Capacitive Electrode Material:         Tantalum         Terminal Type And Quantity:         2 tab, solder lug         Shelf Life:         N/a         Unit Of Measure:         -         Permillatrization:         No         Fig:		
Reliable         Not established         Body Length:         7.3 millimeters         Body Width:         4.3 millimeters         Body Height:         4.1 millimeters         Schematic Diagram Designator:         No common or grounded electrode (s)         Electrical Polarization:         Nonpolarized         Brd         Z2.0 microfarads single section         22.0 microfarads single section         Pati         Dady and Stong Per Section:         23.0 d single section         Anderated Operating Temp:         Between -55.0 degrees celsius and 85.0 degrees celsius         Nonderated Continuous Voltage Rating And Type Per Section:         10.0 to 10.0 percent single section         Z3.0 d single section         Pationt         Totaratum         Terminal Type And Quantity:         2 tab, solder lug         Shelf Life:         N/a         Unit of Measure:         -         Demilitarization:         No         Pinitiarization:	Rubbility Indicator:         Not established         Body Length:         7.3 millimeters         Body Width:         4.3 millimeters         Body Height:         4.1 millimeters         Schematic Diagram Designator:         No common or grounded electrode (s)         Electrical Polarization:         Nonpolarized         End Application:         P-1         Capacitance Value Per Section:         22.0 microfarads single section         Pathematic Diagram Designator:         Nonderated Operating Temp:         Between -55.0 degrees celsius and 85.0 degrees celsius         Anderated Continuous Voltage Rating And Type Per Section:         35.0 dc single section         Tolerance Range Per Section:         -10.0 to 10.0 percent single section         Capacitive Electrode Material:         Tantalum         Terminal Type And Quantity:         2 tab, solder lug         Shelf Life:         N/a         Unit Of Measure:         -         Permilltarization:         No         Fig:	Body Style:	
Not established Body Length: 7.3 millimeters Body Width: 4.3 millimeters Body Height: 4.1 millimeters Schematic Diagram Designator: No common or grounded electrode (s) Electrical Polarization: Nonpolarized End Application: B-1 Capacitance Value Per Section: 22.0 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Clerance Range Per Section: - Toterance Inter Section: - Toter	Not established         Body Length:         7.3 millimeters         Body Width:         4.3 millimeters         Body Height:         4.1 millimeters         Schematic Diagram Designator:         No common or grounded electrode (s)         Electrical Polarization:         Nonpolarized         End Application:         Pacapitance Value Per Section:         22.0 microfarads single section         Nonderated Operating Temp:         Between -55.0 degrees celsius and 85.0 degrees celsius         Nonderated Continuous Voltage Rating And Type Per Section:         35.0 dc single section         7.0.0 to 10.0 percent single section         Capacitive Electrode Material:         Tantalum         Terminal Type And Quantity:         2 tab, solder lug         Shelf Life:         N/a         Unit of Measure:         -         -         Pomilitarization:         No         Piniltarization:	Chip type	
Body Length: 7.3 millimeters Body Width: 4.3 millimeters Body Height: 4.1 millimeters Body Height: 4.1 millimeters Schematic Diagram Designator: No common or grounded electrode (s) Electrical Polarization: Nonpolarized End Application: B-1 Capacitance Value Per Section: 22.0 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: 10.0 to 10.0 percent single section Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Body Length: 7.3 millimeters Body Width: 4.3 millimeters Body Height: 4.1 millimeters Body Height: 4.1 millimeters Schematic Diagram Designator: No common or grounded electrode (s) Electrical Polarization: Nonpolarized End Application: B-1 Capacitance Value Per Section: 22.0 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.0 to 10.0 percent single section Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit of Measure:  Demilitarization: No	Reliability Indicator:	
7.3 millimeters Body Width: 4.3 millimeters Body Height: 4.1 millimeters Schematic Diagram Designator: A to common or grounded electrode (s) Electrical Polarization: Nonpolarized End Application: B-1 Capacitance Value Per Section: 22.0 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure: No Fig:	7.3 millimetersBody Width:4.3 millimetersBody Height:4.1 millimetersSchematic Diagram Designator:No common or grounded electrode (s)Electrical Polarization:NonpolarizedEnd Application:B-1Capacitance Value Per Section:22.0 microfarads single sectionNonderated Operating Temp:Between -55.0 degrees celsius and 85.0 degrees celsiusMonderated Continuous Voltage Rating And Type Per Section:35.0 dc single sectionCapacitive Electrode Material:TontalumTerminal Type And Quantity:2 tab, solder lugShelf Life:N/aUnit Of Measure:Pemilitarization:NoFig:	Not established	
Body Width: 4.3 millimeters Body Height: 4.1 millimeters Schematic Diagram Designator: No common or grounded electrode (s) Electrical Polarization: Nonpolarized End Application: B-1 Capacitance Value Per Section: 22.0 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Capacitive Electrode Material: Toltralum Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Body Width: 4.3 millimeters Body Height: 4.1 millimeters Schematic Diagram Designator: No common or grounded electrode (s) Electrical Polarization: Nonpolarized End Application: B-1 Capacitance Value Per Section: 22.0 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Capacitive Electrode Material: Tontalum Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Body Length:	
4.3 millimeters Body Height: 4.1 millimeters Schematic Diagram Designator: No common or grounded electrode (s) Electrical Polarization: Nonpolarized End Application: B-1 Capacitance Value Per Section: 22.0 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 de single section Tolerance Range Per Section: -10.0 to 10.0 percent single section Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	4.3 millimeters Body Height: 4.1 millimeters Schematic Diagram Designator: No common or grounded electrode (s) Electrical Polarization: Nonpolarized End Application: B-1 Capacitance Value Per Section: 22.0 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fijg:	7.3 millimeters	
Body Height: 4.1 millimeters Schematic Diagram Designator: No common or grounded electrode (s) Electrical Polarization: Nonpolarized End Application: B-1 Capacitance Value Per Section: 22.0 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.0 to 10.0 percent single section Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 tab, solder lug Sheff Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Body Height: 4.1 millimeters Schematic Diagram Designator: No common or grounded electrode (s) Electrical Polarization: Nonpolarized End Application: B-1 Capacitance Value Per Section: 22.0 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.0 to 10.0 percent single section Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure: - Demilitarization: No	Body Width:	
4.1 millimeters Schematic Diagram Designator: No common or grounded electrode (s) Electrical Polarization: Nonpolarized End Application: B-1 Capacitance Value Per Section: 22.0 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.0 to 10.0 percent single section Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	4.1 millimeters Schematic Diagram Designator: No common or grounded electrode (s) Electrical Polarization: Nonpolarized End Application: B-1 Capacitance Value Per Section: 22.0 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.0 to 10.0 percent single section Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	4.3 millimeters	
Schematic Diagram Designator: No common or grounded electrode (s) Electrical Polarization: Nonpolarized End Application: B-1 Capacitance Value Per Section: 22.0 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.0 to 10.0 percent single section Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Schematic Diagram Designator: No common or grounded electrode (s) Electrical Polarization: Nonpolarized End Application: B-1 Capacitance Value Per Section: 22.0 microfarads single section 22.0 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.0 to 10.0 percent single section Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Body Height:	
No common or grounded electrode (s) Electrical Polarization: Nonpolarized End Application: B-1 Capacitance Value Per Section: 22.0 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.0 to 10.0 percent single section Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	No common or grounded electrode (s) Electrical Polarization: Nonpolarized End Application: B-1 Capacitance Value Per Section: 22.0 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.0 to 10.0 percent single section Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Init Of Measure:  Demilitarization: No Fig:	4.1 millimeters	
Electrical Polarization: Nonpolarized End Application: B-1 Capacitance Value Per Section: 22.0 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.0 to 10.0 percent single section Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Electrical Polarization: Nonpolarized End Application: B-1 Capacitance Value Per Section: 22.0 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.0 to 10.0 percent single section Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure: - Demilitarization: No	Schematic Diagram Designator:	
Nonpolarized End Application: B-1 Capacitance Value Per Section: 22.0 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.0 to 10.0 percent single section Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Nonpolarized End Application: B-1 Capacitance Value Per Section: 22.0 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.0 to 10.0 percent single section Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	No common or grounded electrode (s)	
End Application: B-1 Capacitance Value Per Section: 22.0 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.0 to 10.0 percent single section Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No	End Application:   B-1   Capacitance Value Per Section:   22.0 microfarads single section   Nonderated Operating Temp:   Between -55.0 degrees celsius and 85.0 degrees celsius   Nonderated Continuous Voltage Rating And Type Per Section:   35.0 dc single section   7olerance Range Per Section:   -10.0 to 10.0 percent single section   Capacitive Electrode Material:   Tantalum   Terminal Type And Quantity:   2 tab, solder lug   Shelf Life:   N/a   Init Of Measure:       Penilitarization:   No   Fig:	Electrical Polarization:	
B-1 Capacitance Value Per Section: 22.0 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.0 to 10.0 percent single section Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No	B-1 Capacitance Value Per Section: 22.0 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.0 to 10.0 percent single section Capacitive Electrode Material: -10.0 to 10.0 percent single section -10.0 to 10.0 to 10.	Nonpolarized	
Capacitance Value Per Section: 22.0 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.0 to 10.0 percent single section Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Capacitance Value Per Section:22.0 microfarads single sectionNonderated Operating Temp:Between -55.0 degrees celsius and 85.0 degrees celsiusNonderated Continuous Voltage Rating And Type Per Section:35.0 dc single sectionTolerance Range Per Section:-10.0 to 10.0 percent single sectionCapacitive Electrode Material:TantalumTerminal Type And Quantity:2 tab, solder lugShelf Life:N/aDemilitarization:Forminal Type And Quantity:Demilitarization:Demilitarization:NoFig:	End Application:	
22.0 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.0 to 10.0 percent single section Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No	22.0 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.0 to 10.0 percent single section Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No	B-1	
Nonderated Operating Temp:   Between -55.0 degrees celsius and 85.0 degrees celsius   Nonderated Continuous Voltage Rating And Type Per Section:   35.0 dc single section   Tolerance Range Per Section:   -10.0 to 10.0 percent single section   Capacitive Electrode Material:   Tantalum   Terminal Type And Quantity:   2 tab, solder lug   Shelf Life:   N/a   Dint Of Measure:     Demilitarization:   No   Fig:	Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.0 to 10.0 percent single section Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Capacitance Value Per Section:	
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.0 to 10.0 percent single section Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.0 to 10.0 percent single section Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No	22.0 microfarads single section	
Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.0 to 10.0 percent single section Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.0 to 10.0 percent single section Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Nonderated Operating Temp:	
35.0 dc single section Tolerance Range Per Section: -10.0 to 10.0 percent single section Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	35.0 dc single section Tolerance Range Per Section: -10.0 to 10.0 percent single section Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Between -55.0 degrees celsius and 85.0 degrees celsius	
Tolerance Range Per Section: -10.0 to 10.0 percent single section Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Tolerance Range Per Section: -10.0 to 10.0 percent single section Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure:  Pemilitarization: No Fiig:	Nonderated Continuous Voltage Rating And Type Per Section:	
-10.0 to 10.0 percent single section Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	-10.0 to 10.0 percent single section Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	35.0 dc single section	
Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Tolerance Range Per Section:	
Tantalum Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Tantalum Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	-10.0 to 10.0 percent single section	
Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Capacitive Electrode Material:	
2 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	2 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Tantalum	
Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Terminal Type And Quantity:	
N/a Unit Of Measure:  Demilitarization: No Fiig:	N/a Unit Of Measure:  Demilitarization: No Fiig:	2 tab, solder lug	
Unit Of Measure:  Demilitarization: No Fiig:	Unit Of Measure:  Demilitarization: No Fiig:	Shelf Life:	
 Demilitarization: No Fiig:	 Demilitarization: No Fiig:	N/a	
Demilitarization: No Fiig:	Demilitarization: No Fiig:	Unit Of Measure:	
No Fiig:	No Fiig:	-	
Fiig:	Fiig:	Demilitarization:	
-	-	No	
A010b0	А010b0	Fiig:	
		A010b0	