Electrolytic Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-650-1704

Chip type Reliability Indicator: Not established Body Length: 7.3 millimeters Body Width: 6.1 millimeters Body Height: 3.45 millimeters Schematic Diagram Designator: No common or grounded electrode (s) Electrical Polarization: Nonopolarized Section Quantity: 1 Capacitance Value Per Section: 330.0 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: -20.0 to 20.0 microfarads single section Capacitive Electrode Material: -20.0 to 20.0 microfarads single section Capacitive Electrode Material: -20.0 to 20.0 microfarads single section Capacitive Electrode Material: Tartalum Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: - Pemilitarization: No Fiig:	Bod	ly Style:
Not established Body Length: 7.3 millimeters Body Width: 6.1 millimeters Body Height: 3.45 millimeters Schematic Diagram Designator: No common or grounded electrode (s) Electrical Polarization: Nonpolarized Section Quantity: 1 Capacitance Value Per Section: 330.0 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 10.0 dc single section Polarized Per Section: -20.0 to 20.0 microfarads single section Capacitive Electrode Material: -20.0 to 20.0 microfarads single section Capacitive Electrode Material: Tatalum Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: - - Demilitarization: No Fig:		
Not established Body Length: 7.3 millimeters Body Width: 6.1 millimeters Body Height: 3.45 millimeters Schematic Diagram Designator: No common or grounded electrode (s) Electrical Polarization: Nonpolarized Section Quantity: 1 Capacitance Value Per Section: 330.0 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 10.0 de single section 20.0 to 20.0 microfarads single section 2.0.0 to 20.0 microfarads single section Capacitive Electrode Material: 2.0.0 to 20.0 microfarads single section Capacitive Electrode Material: 2.0.1 to 20.0 microfarads single section Capacitive Electrode Material: 1 Perminal Type And Quantity: 2 bonding pad Sheif Life: Na Unit Of Measure: - Demilitarization: Na Sheif Life: <th>•</th> <th></th>	•	
Body Length: 7.3 millimeters Body Width: 6.1 millimeters Body Height: 3.45 millimeters Schematic Diagram Designator: No common or grounded electrode (s) Electrical Polarization: Nonpolarized Section Quantity: 1 Capacitance Value Per Section: 330.0 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 10.0 dc single section -20.0 to 20.0 microfarads -20.0 to 20.0 microfarads single section -20		-
7.3 millimeters Body Width: 6.1 millimeters Body Height: 3.45 millimeters Schematic Diagram Designator: No common or grounded electrode (s) Electrical Polarization: Nonpolarized Section Quantity: 1 Capacitance Value Per Section: 330.0 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 10.0 dc single section You for ofarads single section 20.0 to 20.0 microfarads single section 20.0 to 20.0 microfarads single section 20.0 to 20.0 microfarads single section Capacitive Electrode Material: You for Measure: 2 bonding pad Shelf Life: N/a Unit Of Measure: Permillarization: No Fig:		
Body Width: 6.1 millimeters Body Height: 3.45 millimeters Schematic Diagram Designator: No common or grounded electrode (s) Electrical Polarization: Nonpolarized Section Quantity: 1 Capacitance Value Per Section: 330.0 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 10.0 dc single section Tolerance Range Per Section: -20.0 to 20.0 microfarads single section Case Material: Metal Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 bonding pad Sheff Life: N/a Unit Of Measure: - Demilitarization: No Fig:		
6.1 millimeters Body Height: 3.45 millimeters Schematic Diagram Designator: No common or grounded electrode (s) Electrical Polarization: Nonpolarized Section Quantity: 1 Capacitance Value Per Section: 330.0 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 10.0 dc single section Tolerance Range Per Section: -20.0 to 20.0 microfarads single section Case Material: Metal Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 bonding pad Sheff Life: N/a Unit Of Measure: Demilitarization: No Fig:	-	
Body Height: 3.45 millimeters Schematic Diagram Designator: No common or grounded electrode (s) Electrical Polarization: Nonpolarized Section Quantity: 1 Capacitance Value Per Section: 330.0 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 10.0 dc single section Tolerance Range Per Section: -20.0 to 20.0 microfarads single section Case Material: Metal Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:		
3.45 millimeters Schematic Diagram Designator: No common or grounded electrode (s) Electrical Polarization: Nonpolarized Section Quantity: 1 Capacitance Value Per Section: 330.0 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 10.0 dc single section Tolerance Range Per Section: -20.0 to 20.0 microfarads single section Case Material: Metal Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	-	
Schematic Diagram Designator: No common or grounded electrode (s) Electrical Polarization: Nonpolarized Section Quantity: 1 Capacitance Value Per Section: 330.0 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 10.0 dc single section Tolerance Range Per Section: -20.0 to 20.0 microfarads single section Case Material: Metal Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Pemilitarization: No		
No common or grounded electrode (s) Electrical Polarization: Nonpolarized Section Quantity: 1 Capacitance Value Per Section: 330.0 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 10.0 dc single section Tolerance Range Per Section: -20.0 to 20.0 microfarads single section Case Material: Metal Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No		
Electrical Polarization: Nonpolarized Section Quantity: 1 Capacitance Value Per Section: 330.0 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 10.0 dc single section Tolerance Range Per Section: -20.0 to 20.0 microfarads single section Case Material: Metal Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No		
Section Quantity: 1 Capacitance Value Per Section: 330.0 microfarads single section Monderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 10.0 dc single section Colerance Range Per Section: -20.0 to 20.0 microfarads single section Case Material: Aetal Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:		
Section Quantity: 1 Capacitance Value Per Section: 330.0 microfarads single section Monderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 10.0 dc single section Colerance Range Per Section: -20.0 to 20.0 microfarads single section Case Material: Aetal Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Non	polarized
1 Capacitance Value Per Section: 330.0 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 10.0 dc single section 70lerance Range Per Section: -20.0 to 20.0 microfarads single section Case Material: Metal Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Dit Of Measure: - Demilitarization: No Fig:		
330.0 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 10.0 dc single section Tolerance Range Per Section: -20.0 to 20.0 microfarads single section Case Material: Metal Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:		
330.0 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 10.0 dc single section Tolerance Range Per Section: -20.0 to 20.0 microfarads single section Case Material: Metal Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	Сар	acitance Value Per Section:
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 10.0 dc single section Tolerance Range Per Section: -20.0 to 20.0 microfarads single section Case Material: Metal Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	330.	.0 microfarads single section
Nonderated Continuous Voltage Rating And Type Per Section: 10.0 dc single section Tolerance Range Per Section: -20.0 to 20.0 microfarads single section Case Material: Metal Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	Non	iderated Operating Temp:
10.0 dc single section Tolerance Range Per Section: -20.0 to 20.0 microfarads single section Case Material: Metal Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Betv	ween -55.0 degrees celsius and 125.0 degrees celsius
Tolerance Range Per Section: -20.0 to 20.0 microfarads single section Case Material: Metal Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	Non	derated Continuous Voltage Rating And Type Per Section:
-20.0 to 20.0 microfarads single section Case Material: Metal Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	10.0) dc single section
Case Material: Metal Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Tole	erance Range Per Section:
Metal Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	-20.	0 to 20.0 microfarads single section
Capacitive Electrode Material: Tantalum Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Cas	e Material:
Tantalum Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Meta	al
Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Сар	acitive Electrode Material:
2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Tan	talum
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terr	minal Type And Quantity:
N/a Unit Of Measure: Demilitarization: No Fiig:	2 bo	onding pad
Unit Of Measure: Demilitarization: No Fiig:	She	If Life:
 Demilitarization: No Fiig:	N/a	
No Fiig:	Unit	t Of Measure:
No Fiig:		
Fiig:	Den	nilitarization:
-	No	
A010b0	Fiig	:
	A01	0b0