NSN 5910-01-650-8327

Ceramic Dielectric Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-650-8327
Body Style:
Chip type
Reliability Indicator:
Not established
Body Length:
1.0 millimeters
Body Width:
0.50 millimeters
Body Height:
0.56 millimeters
Schematic Diagram Designator:
No common or grounded electrode (s)
Section Quantity:
1
Capacitance Value Per Section:
470.0 picofarads single section
Nonderated Operating Temp:
Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius
Between -55.0 degrees celsius and 125.0 degrees celsius
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section:
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section:
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -5.0 to 5.0 picofarads single section
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -5.0 to 5.0 picofarads single section Case Material:
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -5.0 to 5.0 picofarads single section Case Material: Ceramic
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -5.0 to 5.0 picofarads single section Case Material: Ceramic Terminal Type And Quantity:
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -5.0 to 5.0 picofarads single section Case Material: Ceramic Terminal Type And Quantity: 2 bonding pad
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -5.0 to 5.0 picofarads single section Case Material: Ceramic Terminal Type And Quantity: 2 bonding pad Shelf Life:
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -5.0 to 5.0 picofarads single section Case Material: Ceramic Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -5.0 to 5.0 picofarads single section Case Material: Ceramic Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -5.0 to 5.0 picofarads single section Case Material: Ceramic Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure:
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -5.0 to 5.0 picofarads single section Case Material: Ceramic Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: