

View Online at https://aerobasegroup.com/nsn/5910-01-651-0928

Body Style:   Chip type   Reliability Indicator:   Not established   Body Length:   1.00 millimeters   Body Width:   0.50 millimeters   Body Height:   0.50 millimeters   Schematic Diagram Designator:   No common or grounded electrode (s)   End Application:   Shop equipment   Section Quantity:   1   Capacitance Value Per Section:   1000.0 picofarads single section   Nonderated Operating Temp:   Between -55.0 degrees celsius and 125.0 degrees celsius   Nonderated Continuous Voltage Rating And Type Per Section:   1:0 of 5.0 percent single section   Case Material:   Ceramic   Terminal Type And Quantity:   2 bonding pad   Shelf Life:   Na   Pillitarization:     Na   Filig:   A010b0		
Reliability Indicator:         Not established         Body Length:         1.00 millimeters         Body Width:         0.50 millimeters         Body Height:         0.50 millimeters         Schematic Diagram Designator:         No common or grounded electrode (s)         End Application:         Shop equipment         Section Quantity:         1         Cappitance Value Per Section:         1000.0 picofarads single section         1000.0 picofarads single section         1000.0 picofarads single section         10.0 o continuous Voltage Rating And Type Per Section:         10.0 d c single section         10.0 d single section         10.0 d single	Body Style:	
Not established         Body Length:         1.00 millimeters         Body Width:         0.50 millimeters         Body Height:         0.50 millimeters         Schematic Diagram Designator:         No common or grounded electrode (s)         End Application:         Shop equipment         Section Quantity:         1         Capacitance Value Per Section:         1000.0 picofarads single section         1000.0 picofarads single section         1000.0 picofarads single section         16.0 d c single section         16.0 d c single section         16.0 d c single section         17.0 Carance Range Per Section:         18.0 d c single section         19.0 d c single section         10.0 d c single section	Chip type	
Body Length:1.00 millimetersBody Width:0.50 millimetersBody Height:0.50 millimetersSchematic Diagram Designator:No common or grounded electrode (s)End Application:Shop equipmentSection Quantity:1Capacitance Value Per Section:1000.0 picofarads single sectionModerated Operating Temp:Between -55.0 degrees celsius and 125.0 degrees celsiusNonderated Continuous Voltage Rating And Type Per Section:15.0 to 5.0 percent single sectionCaparice Range Per Section:6.5.0 to 5.0 percent single sectionCaramicCeramicSectioning padShelf Life:N/aUif of Measure:Permilitarization:NoFig:	Reliability Indicator:	
1.00 millimeters         Body Width:         0.50 millimeters         Body Height:         0.50 millimeters         Schematic Diagram Designator:         No common or grounded electrode (s)         End Application:         Shop equipment         Section Quantity:         1         Capacitance Value Per Section:         1000.0 picofarads single section         Nonderated Operating Temp:         Between -55.0 degrees celsius and 125.0 degrees celsius         Nonderated Continuous Voltage Rating And Type Per Section:         16.0 dc single section         Caparace Range Per Section:         -55.0 to 5.0 percent single section         Caramic         Ceramic         Va         Naterial:         2 bonding pad         Shelf Life:         N/a         Unit of Measure:         -         Demilitarization:         No         Fig:	Not established	
Body Width: 0.50 millimeters Body Height: 0.50 millimeters Schematic Diagram Designator: No common or grounded electrode (s) End Application: Shop equipment Section Quantity: 1 Capacitance Value Per Section: 1000.0 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 16.0 dc single section Tolerance Range Per Section: -5.0 to 5.0 percent single section Case Material: Ceramic Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fiig:	Body Length:	
0.50 millimeters Body Height: 0.50 millimeters Schematic Diagram Designator: No common or grounded electrode (s) End Application: Shop equipment Section Quantity: 1 Capacitance Value Per Section: 1000.0 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 16.0 dc single section Tolerance Range Per Section: -5.0 to 5.0 percent single section Case Material: Ceramic Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	1.00 millimeters	
Body Height: 0.50 millimeters Schematic Diagram Designator: No common or grounded electrode (s) End Application: Shop equipment Section Quantity: 1 Capacitance Value Per Section: 1000.0 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 16.0 dc single section Tolerance Range Per Section: -5.0 to 5.0 percent single section Case Material: Ceramic Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	Body Width:	
0.50 millimeters Schematic Diagram Designator: No common or grounded electrode (s) End Application: Shop equipment Section Quantity: 1 Capacitance Value Per Section: 1000.0 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 16.0 dc single section Tolerance Range Per Section: -5.0 to 5.0 percent single section Case Material: Ceramic Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	0.50 millimeters	
Schematic Diagram Designator: No common or grounded electrode (s) End Application: Shop equipment Section Quantity: 1 Capacitance Value Per Section: 1000.0 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 16.0 dc single section Tolerance Range Per Section: -5.0 to 5.0 percent single section Case Material: Ceramic Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Body Height:	
No common or grounded electrode (s) End Application: Shop equipment Section Quantity: 1 Capacitance Value Per Section: 1000.0 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 16.0 dc single section Tolerance Range Per Section: -5.0 to 5.0 percent single section Case Material: Ceramic Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	0.50 millimeters	
End Application: Shop equipment Section Quantity: 1 Capacitance Value Per Section: 1000.0 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 16.0 dc single section Tolerance Range Per Section: -5.0 to 5.0 percent single section Case Material: Ceramic Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Schematic Diagram Designator:	
Shop equipment Section Quantity: 1  Capacitance Value Per Section: 1000.0 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 16.0 dc single section Tolerance Range Per Section: -5.0 to 5.0 percent single section Case Material: Ceramic Ceramic Shoel Life: N/a Unit Of Measure: Demilitarization: No Fig:	No common or grounded electrode (s)	
Section Quantity: 1 Capacitance Value Per Section: 1000.0 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 16.0 dc single section Tolerance Range Per Section: -5.0 to 5.0 percent single section Case Material: Ceramic Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	End Application:	
1         Capacitance Value Per Section:         1000.0 picofarads single section         Nonderated Operating Temp:         Between -55.0 degrees celsius and 125.0 degrees celsius         Nonderated Continuous Voltage Rating And Type Per Section:         16.0 dc single section         Tolerance Range Per Section:         -5.0 to 5.0 percent single section         Case Material:         Ceramic         Terminal Type And Quantity:         2 bonding pad         Shelf Life:         N/a         Unit Of Measure:         -         -         Pemilitarization:         No         Fig:	Shop equipment	
Capacitance Value Per Section: 1000.0 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 16.0 dc single section Tolerance Range Per Section: -5.0 to 5.0 percent single section Case Material: Ceramic Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Section Quantity:	
1000.0 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 16.0 dc single section Tolerance Range Per Section: -5.0 to 5.0 percent single section Case Material: Ceramic Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure:  Demilitarization: No	1	
Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 16.0 dc single section Tolerance Range Per Section: -5.0 to 5.0 percent single section Case Material: Ceramic Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Capacitance Value Per Section:	
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 16.0 dc single section Tolerance Range Per Section: -5.0 to 5.0 percent single section Case Material: Ceramic Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure:  Demilitarization: No	1000.0 picofarads single section	
Nonderated Continuous Voltage Rating And Type Per Section: 16.0 dc single section Tolerance Range Per Section: -5.0 to 5.0 percent single section Case Material: Ceramic Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Nonderated Operating Temp:	
16.0 dc single section Tolerance Range Per Section: -5.0 to 5.0 percent single section Case Material: Ceramic Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Between -55.0 degrees celsius and 125.0 degrees celsius	
Tolerance Range Per Section:   -5.0 to 5.0 percent single section   Case Material:   Ceramic   Terminal Type And Quantity:   2 bonding pad   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fig:	Nonderated Continuous Voltage Rating And Type Per Section:	
-5.0 to 5.0 percent single section Case Material: Ceramic Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure:  Pemilitarization: No Fiig:	16.0 dc single section	
Case Material: Ceramic Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Tolerance Range Per Section:	
Ceramic Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	-5.0 to 5.0 percent single section	
Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Case Material:	
2 bonding pad Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:		
Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Terminal Type And Quantity:	
N/a Unit Of Measure:  Demilitarization: No Fiig:		
Unit Of Measure:  Demilitarization: No Fiig:		
 Demilitarization: No Fiig:		
No Fiig:	Unit Of Measure:	
No Fiig:		
Fiig:		
-		
A010b0	Fiig:	
	A010b0	