

View Online at <https://aerobasegroup.com/nsn/5915-00-000-0148>

Overall Height:

0.650 inches

Body Length:

2.000 inches

Body Width:

0.500 inches

Body Height:

0.400 inches

Unthreaded Mounting Hole Diameter:

0.125 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.770 inches

Vibration Resistance Range In Hertz:

+14.0 to 200.0

Operating Temperature Range:

-25.0 to 167.0 degrees fahrenheit

Average Life Rating In Hours:

9000000.0

Reference Frequency Per Function:

20.0 megahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Principal Circuitry Type Per Function:

Crystal blank

Average Power Rating Per Function:

0.1 watts blank

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 unthreaded hole

Features Provided:

Moisture resistant and mounting bracket

Insertion Loss At Reference Frequency Per Function In Decibels:

5.0 blank

Functional Terminal Type And Quantity:

1 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

15.00 megahertz blank and 19.99 megahertz blank and 20.00 megahertz blank and 25.00 megahertz blank

Body Material:

Metal

Frequency Band Width Per Function:

19.997 megahertz blank and 20.003 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 50.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

19.997 megahertz blank and 20.003 megahertz blank

Body Surface Treatment:

Tin

Unpackaged Unit Weight:

0.125 ounces

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0