

View Online at <https://aerobasegroup.com/nsn/5915-00-001-7234>

Overall Height:

0.850 inches

Body Length:

2.030 inches

Body Width:

0.780 inches

Body Height:

0.600 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.615 inches

Vibration Resistance Range In Hertz:

+10.0 to 500.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.450 inches

Operating Temperature Range:

-30.0 to 85.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

8.0 kilohertz blank

Input Impedance Per Function W/load:

1.0 kilohms blank

Output Impedance Per Function W/source Across Input:

1.0 kilohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 terminal

Insertion Loss At Reference Frequency Per Function In Decibels:

6.0 blank

Functional Terminal Type And Quantity:

2 pin ground 3rd function

Specified Frequencies Of Discrimination Per Function:

6.30 kilohertz blank and 38.00 kilohertz blank and 90.00 kilohertz blank and 5.00 megahertz blank

Body Material:

Metal

Frequency Band Width Per Function:

6.30 kilohertz blank and 38.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

1.0 blank and 1.0 blank and 46.0 blank and 46.0 blank

Maximum Dielectric Withstanding Dc Voltage:

100.0 volts at sea level

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0