

View Online at https://aerobasegroup.com/nsn/5915-00-003-7764

Overall Length:
0.788 inches
Body Length:
0.598 inches
Body Outside Diameter:
0.406 inches
Vibration Resistance Range In Hertz:
+10.0 to 2000.0
Operating Tempurature Range:
-55.0 to 85.0 degrees celsius
Average Life Rating In Hours:
1000.0
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Operating Current Rating Per Function In Amps:
1.0 blank
Principal Circuitry Type Per Function:
Inductance-capacitance blank
Mounting Facility Screw Thread Series Designator:
Unf
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
1 threaded bushing
1 threaded bushing
1 threaded bushing Functional Terminal Type And Quantity:
1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function
1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function:
1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 150.0 volts dc blank
1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 150.0 volts dc blank Thread Size:
1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 150.0 volts dc blank Thread Size: 0.250 inches
1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 150.0 volts dc blank Thread Size: 0.250 inches Maximum Dielectric Withstanding Dc Voltage:
1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 150.0 volts dc blank Thread Size: 0.250 inches Maximum Dielectric Withstanding Dc Voltage: 300.0 volts at sea level
1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 150.0 volts dc blank Thread Size: 0.250 inches Maximum Dielectric Withstanding Dc Voltage: 300.0 volts at sea level Style Designator:
1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 150.0 volts dc blank Thread Size: 0.250 inches Maximum Dielectric Withstanding Dc Voltage: 300.0 volts at sea level Style Designator: Round terminal/terminals on opposite surfaces
1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 150.0 volts dc blank Thread Size: 0.250 inches Maximum Dielectric Withstanding Dc Voltage: 300.0 volts at sea level Style Designator: Round terminal/terminals on opposite surfaces Shelf Life:
1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 150.0 volts dc blank Thread Size: 0.250 inches Maximum Dielectric Withstanding Dc Voltage: 300.0 volts at sea level Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a

No

NSN 5915-00-003-7764

Radio Frequency Interference Filter - Page 2 of 2

Fiig: A047b0

