

View Online at <https://aerobasegroup.com/nsn/5915-00-003-7796>

Overall Height:

2.250 inches

Body Length:

3.000 inches

Body Width:

0.800 inches

Body Height:

2.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.562 inches

Vibration Resistance Range In Hertz:

+10.0 to 55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.562 inches

Operating Temperature Range:

-55.0 to 100.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

400.0 hertz blank

Source Impedance Rating Per Function:

100.0 kilohms blank

Load Impedance Per Function:

100.0 kilohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

0.2 blank

Functional Terminal Type And Quantity:

2 wire hook output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

100.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

200.00 hertz blank and 388.00 hertz blank and 412.00 hertz blank and 1.20 kilohertz blank

Thread Size:

0.138 inches

Body Material:

Metal

Frequency Band Width Per Function:

388.00 hertz blank and 412.00 hertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

24.0 blank and 1.0 blank and 1.0 blank and 24.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0