

View Online at <https://aerobasegroup.com/nsn/5915-00-004-5852>

Overall Height:

0.547 inches

Body Length:

0.525 inches

Body Width:

0.410 inches

Body Height:

0.360 inches

Operating Temperature Range:

-50.0 to 70.0 degrees celsius

Reference Frequency Per Function:

470.0 kilohertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

3 terminal

Features Provided:

Fungus resistant and moisture resistant

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

Functional Terminal Type And Quantity:

1 pin input 1st function 2 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

460.60 kilohertz blank and 465.30 kilohertz blank and 474.70 kilohertz blank and 479.40 kilohertz blank

Body Material:

Plastic

Frequency Band Width Per Function:

465.30 kilohertz blank and 474.70 kilohertz blank

Discrimination At Specification Frequencies Per Function In Decibels:

3.0 blank and 60.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

465.3 kilohertz blank and 474.7 kilohertz blank

Criticality Code Justification:

Feat

Special Features:

As differentiated by circuit test for q-factor; inductor tapped

Unpackaged Unit Weight:

2.000 ounces

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0