NSN 5915-00-005-2617

Band Pass Filter - Page 1 of 2



band pass and 484.525 kilohertz 2nd band

View Online at https://aerobasegroup.com/nsn/5915-00-005-2617

| Overall Length: |
|---|
| 1.510 inches |
| Overall Height: |
| 0.595 inches |
| Body Length: |
| 1.510 inches |
| Body Width: |
| 1.120 inches |
| Vibration Resistance Range In Hertz: |
| +10.0 to 2000.0 |
| Operating Tempurature Range: |
| -20.0/+71.0 degrees celsius |
| Reference Frequency Per Function: |
| 483.425 single radio interference pulses per second |
| Source Impedance Rating Per Function: |
| 50.0 ohms 2nd band pass 2nd function |
| Load Impedance Per Function: |
| 50.0 ohms 2nd band pass 2nd function |
| Principal Circuitry Type Per Function: |
| Crystal 2nd band pass 2nd function |
| Inclosure Type: |
| Encased |
| Mounting Facility Type And Quantity: |
| 7 terminal |
| Insertion Loss At Reference Frequency Per Function In Decibels: |
| 3.0 2nd band pass 2nd function |
| Functional Terminal Type And Quantity: |
| 4 pin output 2nd function |
| Specificationified Frequencies Of Discrimination Per Function: |
| 482.925 kilohertz 2nd band pass and 483.70 kilohertz 2nd band pass and 483.75 kilohertz 2nd band pass |
| pass 2nd function |
| Frequency Band Width Per Function: |
| 483.70 kilohertz 2nd band pass and 483.75 kilohertz 2nd band pass 2nd function |
| Discrimination At Specificationified Frequencies Per Function In Decibels: |
| 30.0 1st band pass and 1.5 1st band pass and 1.5 1st band pass and 30.0 1st band pass 1st function |
| Style Designator: |
| Rectangular terminal/terminals on opposite surfaces |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| |

No

NSN 5915-00-005-2617

Band Pass Filter - Page 2 of 2

Fiig: A047b0

