NSN 5915-00-005-3311



Low Pass Filter - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5915-00-005-3311 **Overall Length:** 0.968 inches **Body Length:** 0.406 inches **Body Outside Diameter:** 0.350 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Reference Frequency Per Function:** 12.5 megahertz blank **Source Impedance Rating Per Function:** 0.01 ohms blank **Mounting Facility Screw Thread Series Designator:** Unf **Inclosure Type:** Hermetically sealed Width Across Flats: 0.250 inches **Mounting Facility Type And Quantity:** 1 threaded bushing 3rd function Insertion Loss At Reference Frequency Per Function In Decibels: 15.0 blank **Functional Terminal Type And Quantity:** 1 tab, solder lug output 2nd function **Specified Frequencies Of Discrimination Per Function:** 5.00 megahertz 1st low pass **Thread Size:** 0.250 inches **Frequency Band Width Per Function:** 5.00 megahertz blank and 21.66 megahertz blank Discrimination At Specificationified Frequencies Per Function In Decibels: 15.0 blank and 60.0 blank **Maximum Dielectric Withstanding Dc Voltage:** 100.0 volts at sea level **Style Designator:** Round terminal/terminals on opposite surfaces **Test Data Document:** 98230-0n089567 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life:

Unit Of Measure:

N/a

NSN 5915-00-005-3311

Low Pass Filter - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A047b0