

View Online at <https://aerobasegroup.com/nsn/5915-00-005-3311>

Overall Length:

0.968 inches

Body Length:

0.406 inches

Body Outside Diameter:

0.350 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Reference Frequency Per Function:

12.5 megahertz blank

Source Impedance Rating Per Function:

0.01 ohms blank

Mounting Facility Screw Thread Series Designator:

Unf

Inclosure Type:

Hermetically sealed

Width Across Flats:

0.250 inches

Mounting Facility Type And Quantity:

1 threaded bushing 3rd function

Insertion Loss At Reference Frequency Per Function In Decibels:

15.0 blank

Functional Terminal Type And Quantity:

1 tab, solder lug output 2nd function

Specified Frequencies Of Discrimination Per Function:

5.00 megahertz 1st low pass

Thread Size:

0.250 inches

Frequency Band Width Per Function:

5.00 megahertz blank and 21.66 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

15.0 blank and 60.0 blank

Maximum Dielectric Withstanding Dc Voltage:

100.0 volts at sea level

Style Designator:

Round terminal/terminals on opposite surfaces

Test Data Document:

98230-0n089567 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A047b0