

View Online at <https://aerobasegroup.com/nsn/5915-00-005-7060>

**Overall Length:**

1.082 inches

**Body Length:**

0.540 inches

**Body Outside Diameter:**

0.415 inches

**Vibration Resistance Range In Hertz:**

+10.0/+2000.0

**Operating Temperature Range:**

-55.0 to 85.0 degrees celsius

**Average Life Rating In Hours:**

250.0

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Power Line Frequency Rating Per Function In Hertz:**

400.0 blank

**Operating Current Rating Per Function In Amps:**

5.0 blank

**Maximum Voltage Drop Per Function:**

150.0 millivolts ac blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Maximum Temperature Rise:**

35.0 degrees celsius

**Full Load Insertion Loss Frequencies In Megahertz:**

0.1 and 0.3 and 0.5 and 1.0 and 3.0 and 1000.0

**Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:**

0.0 and 5.0 and 22.0 and 45.0 and 70.0 and 70.0

**Mounting Facility Screw Thread Series Designator:**

Unf

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Functional Terminal Type And Quantity:**

1 tab, solder lug output 2nd function

**Operating Voltage Rating And Type Per Function:**

125.0 volts ac blank and 150.0 volts dc blank

**Thread Size:**

0.250 inches

**Maximum Dielectric Withstanding Dc Voltage:**

500.0 volts at sea level

**Unpackaged Unit Weight:**

8.000 grams

**Style Designator:**

Round terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0