

View Online at <https://aerobasegroup.com/nsn/5915-00-006-9101>

Overall Height:

3.843 inches

Body Length:

1.750 inches

Body Width:

1.750 inches

Body Height:

3.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.250 inches

Vibration Resistance Range In Hertz:

+10.0 to 55.0

Operating Temperature Range:

-55.0 to 85.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

988.0 hertz blank

Source Impedance Rating Per Function:

10.0 kilohms blank

Load Impedance Per Function:

10.0 kilohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

7.0 blank

Functional Terminal Type And Quantity:

1 turret output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

100.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

881.00 hertz blank and 882.00 hertz blank and 1.038 kilohertz blank and 1.088 kilohertz blank

Thread Size:

0.138 inches

Frequency Band Width Per Function:

882.00 hertz blank and 1.038 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

30.0 blank and 3.0 blank and 3.0 blank and 30.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0