

View Online at <https://aerobasegroup.com/nsn/5915-00-007-7131>

Overall Height:

0.695 inches

Body Length:

1.510 inches

Body Width:

1.120 inches

Body Height:

0.595 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 1.235 inches and 1.245 inches

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.840 inches and 0.860 inches

Operating Temperature Range:

-20.0 to 71.0 degrees celsius

Reference Frequency Per Function:

478.025 kilohertz 1st band pass 1st function

Source Impedance Rating Per Function:

100.0 ohms 2nd band pass 2nd function

Load Impedance Per Function:

168.0 kilohms 2nd band pass 2nd function

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

7 terminal

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 2nd band pass 2nd function

Functional Terminal Type And Quantity:

4 pin output 2nd function

Specificationified Frequencies Of Discrimination Per Function:

477.225 kilohertz 1st band pass and 478.00 kilohertz 1st band pass and 478.05 kilohertz 1st band pass and 478.825 kilohertz 1st band pass 1st function

Body Material:

Metal

Frequency Band Width Per Function:

478.30 kilohertz 2nd band pass and 478.35 kilohertz 2nd band pass

Discrimination At Specificationified Frequencies Per Function In Decibels:

30.0 1st band pass and 1.5 1st band pass and 1.5 1st band pass and 30.0 1st band pass 1st function

Unpackaged Unit Weight:

42.000 grams

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0