

View Online at <https://aerobasegroup.com/nsn/5915-00-007-7132>

**Overall Height:**

0.695 inches

**Body Length:**

1.510 inches

**Body Width:**

1.120 inches

**Body Height:**

0.595 inches

**Unthreaded Mounting Hole Diameter:**

0.188 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.200 inches

**Vibration Resistance Range In Hertz:**

+10.0 to 2000.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.300 inches

**Operating Temperature Range:**

-20.0 to 71.0 degrees celsius

**Reference Frequency Per Function:**

479.375 single radio interference two phase to two phase

**Source Impedance Rating Per Function:**

100.0 ohms 2nd band pass

**Load Impedance Per Function:**

160.0 ohms 2nd band pass

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Insertion Loss At Reference Frequency Per Function In Decibels:**

3.0 2nd band pass

**Functional Terminal Type And Quantity:**

4 pin output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

478.375 kilohertz 2nd band pass 2nd function and 479.35 kilohertz 2nd band pass 2nd function and 479.40 kilohertz 2nd band pass 2nd function and 480.175 kilohertz 2nd band pass 2nd function

**Body Material:**

Metal

**Frequency Band Width Per Function:**

479.35 kilohertz 2nd band pass and 479.40 kilohertz 2nd band pass

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

30.0 2nd band pass and 1.5 2nd band pass and 1.5 2nd band pass and 30.0 2nd band pass 2nd function

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0