

View Online at <https://aerobasegroup.com/nsn/5915-00-007-7132>

Overall Height:

0.695 inches

Body Length:

1.510 inches

Body Width:

1.120 inches

Body Height:

0.595 inches

Unthreaded Mounting Hole Diameter:

0.188 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.200 inches

Vibration Resistance Range In Hertz:

+10.0 to 2000.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.300 inches

Operating Temperature Range:

-20.0 to 71.0 degrees celsius

Reference Frequency Per Function:

479.375 single radio interference two phase to two phase

Source Impedance Rating Per Function:

100.0 ohms 2nd band pass

Load Impedance Per Function:

160.0 ohms 2nd band pass

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 unthreaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 2nd band pass

Functional Terminal Type And Quantity:

4 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

478.375 kilohertz 2nd band pass 2nd function and 479.35 kilohertz 2nd band pass 2nd function and 479.40 kilohertz 2nd band pass 2nd function and 480.175 kilohertz 2nd band pass 2nd function

Body Material:

Metal

Frequency Band Width Per Function:

479.35 kilohertz 2nd band pass and 479.40 kilohertz 2nd band pass

Discrimination At Specificationified Frequencies Per Function In Decibels:

30.0 2nd band pass and 1.5 2nd band pass and 1.5 2nd band pass and 30.0 2nd band pass 2nd function

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0