

View Online at <https://aerobasegroup.com/nsn/5915-00-007-7722>

Overall Length:

7.219 inches

Body Outside Diameter:

1.188 inches

Unthreaded Mounting Hole Diameter:

0.125 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.906 inches

Vibration Resistance Range In Hertz:

+10.0 to 500.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.906 inches

Operating Temperature Range:

-54.0 to 125.0 degrees celsius

Reference Frequency Per Function:

1.085 megahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Input Impedance Per Function W/load:

50.0 ohms blank

Output Impedance Per Function W/source Across Input:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 unthreaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

Functional Terminal Type And Quantity:

1 connector, receptacle output 2nd function

Specified Frequencies Of Discrimination Per Function:

950.00 gigahertz blank and 1.22 gigahertz blank and 1.75 gigahertz blank and 11.00 gigahertz blank

Body Material:

Metal

Frequency Band Width Per Function:

950.00 megahertz blank and 1.22 gigahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

0.5 blank and 0.7 blank and 65.0 blank and 65.0 blank

Style Designator:

Round terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0