

View Online at <https://aerobasegroup.com/nsn/5915-00-008-0339>

Overall Height:

0.695 inches

Body Length:

1.510 inches

Body Width:

1.120 inches

Body Height:

0.595 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 1.235 inches and 1.245 inches

Vibration Resistance Range In Hertz:

+10.0 to 2000.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.840 inches and 0.860 inches

Operating Temperature Range:

-20.0 to 71.0 degrees celsius

Reference Frequency Per Function:

485.975 kilohertz 2nd band pass 2nd function

Source Impedance Rating Per Function:

100.0 ohms 2nd band pass 2nd function

Load Impedance Per Function:

168.0 kilohms 2nd band pass 2nd function

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

7 terminal

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 2nd band pass 2nd function

Functional Terminal Type And Quantity:

4 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

485.175 kilohertz 2nd band pass 2nd function and 485.95 kilohertz 2nd band pass 2nd function and 486.00 kilohertz 2nd band pass 2nd function and 486.775 kilohertz 2nd band pass 2nd function

Body Material:

Metal

Frequency Band Width Per Function:

485.95 kilohertz 2nd band pass and 486.00 kilohertz 2nd band pass 2nd function

Discrimination At Specificationified Frequencies Per Function In Decibels:

30.0 2nd band pass 2nd function and 1.5 2nd band pass 2nd function and 1.5 2nd band pass 2nd function and 30.0 2nd band pass 2nd function

Unpackaged Unit Weight:

42.000 grams

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0