

View Online at <https://aerobasegroup.com/nsn/5915-00-012-4231>

Overall Height:

1.420 inches

Body Length:

2.000 inches

Body Width:

1.000 inches

Body Height:

1.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.600 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.600 inches

Operating Temperature Range:

-0.0 to 60.0 degrees celsius

Reference Frequency Per Function:

469.655 single radio interference two phase to two phase

Source Impedance Rating Per Function:

2.2 kilohms 2nd band pass

Load Impedance Per Function:

2.2 kilohms 2nd band pass 2nd function

Principal Circuitry Type Per Function:

Crystal 2nd band pass 2nd function

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

3.5 2nd band pass

Functional Terminal Type And Quantity:

3 pin ground 3rd function

Maximum Dielectric Withstanding Ac Rms Voltage:

50.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

469.405 kilohertz 2nd band pass 2nd function and 469.63 kilohertz 2nd band pass 2nd function and 469.68 kilohertz 2nd band pass 2nd function and 469.905 kilohertz 2nd band pass 2nd function

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

469.63 kilohertz 2nd band pass and 469.68 kilohertz 2nd band pass

Discrimination At Specificationified Frequencies Per Function In Decibels:

20.0 2nd band pass 2nd function and 3.0 2nd band pass 2nd function and 3.0 2nd band pass 2nd function and 20.0 2nd band pass 2nd function

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0