## NSN 5915-00-013-9623

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-013-9623

**Overall Height:** 

Between 3.141 inches and 3.171 inches

**Body Length:** 

Between 2.000 inches and 2.015 inches

**Body Width:** 

Between 1.422 inches and 1.452 inches

**Body Height:** 

Between 2.578 inches and 2.608 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 0.807 inches and 0.817 inches

**Vibration Resistance Range In Hertz:** 

+10.0 to 2000.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.922 inches and 0.952 inches

**Operating Tempurature Range:** 

-55.0 to 105.0 degrees celsius

**Average Life Rating In Hours:** 

10000.0

**Reference Frequency Per Function:** 

1.0 hertz blank

**Source Impedance Rating Per Function:** 

600.0 ohms blank

**Load Impedance Per Function:** 

600.0 ohms blank

Input Impedance Per Function W/load:

600.0 ohms blank

**Output Impedance Per Function W/source Across Input:** 

600.0 ohms blank

**Principal Circuitry Type Per Function:** 

Inductance-capacitance blank

Mounting Facility Screw Thread Series Designator:

Unf

**Inclosure Type:** 

Encased

**Mounting Facility Type And Quantity:** 

2 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

1.0 blank

**Functional Terminal Type And Quantity:** 

2 tab, solder lug output 2nd function

**Specified Frequencies Of Discrimination Per Function:** 

1.00 hertz blank and 2.40 kilohertz blank and 4.00 kilohertz blank and 5.00 kilohertz blank

## **NSN 5915-00-013-9623** Low Pass Filter - Page 2 of 2



Thread Size:	
0.190 inches	
Body Material:	
Metal	
Frequency Band Width Per Function:	
1.00 hertz blank and 2.40 kilohertz blank	
Discrimination At Specificationified Frequencies Per Function In Decibels:	
3.0 blank and 3.0 blank and 27.0 blank and 37.0 blank	
Style Designator:	
Rectangular terminal/terminals on one surface	
Test Data Document:	
31349-milf18327-12 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification	
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
Yes - demil/mli	
Filg:	
A047b0	