

View Online at <https://aerobasegroup.com/nsn/5915-00-013-9623>

Overall Height:

Between 3.141 inches and 3.171 inches

Body Length:

Between 2.000 inches and 2.015 inches

Body Width:

Between 1.422 inches and 1.452 inches

Body Height:

Between 2.578 inches and 2.608 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 0.807 inches and 0.817 inches

Vibration Resistance Range In Hertz:

+10.0 to 2000.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.922 inches and 0.952 inches

Operating Temperature Range:

-55.0 to 105.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

1.0 hertz blank

Source Impedance Rating Per Function:

600.0 ohms blank

Load Impedance Per Function:

600.0 ohms blank

Input Impedance Per Function W/load:

600.0 ohms blank

Output Impedance Per Function W/source Across Input:

600.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Mounting Facility Screw Thread Series Designator:

Unf

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

1.0 blank

Functional Terminal Type And Quantity:

2 tab, solder lug output 2nd function

Specified Frequencies Of Discrimination Per Function:

1.00 hertz blank and 2.40 kilohertz blank and 4.00 kilohertz blank and 5.00 kilohertz blank

Thread Size:

0.190 inches

Body Material:

Metal

Frequency Band Width Per Function:

1.00 hertz blank and 2.40 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 3.0 blank and 27.0 blank and 37.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Test Data Document:

81349-milf18327-12 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A047b0