

View Online at <https://aerobasegroup.com/nsn/5915-00-013-9740>

Overall Height:

1.420 inches

Body Length:

2.000 inches

Body Width:

1.000 inches

Body Height:

1.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.600 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.600 inches

Operating Temperature Range:

+0.0 to 60.0 degrees celsius

Reference Frequency Per Function:

469.7 kilohertz blank

Source Impedance Rating Per Function:

2.2 kilohms blank

Load Impedance Per Function:

2.2 kilohms blank

Principal Circuitry Type Per Function:

Crystal blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

3.5 blank

Functional Terminal Type And Quantity:

3 pin output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

50.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

469.45 kilohertz blank and 469.68 kilohertz blank and 469.73 kilohertz blank and 469.95 kilohertz blank

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

469.68 kilohertz blank and 469.73 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

20.0 blank and 3.0 blank and 3.0 blank and 20.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0