

View Online at <https://aerobasegroup.com/nsn/5915-00-020-8366>

Overall Height:

1.375 inches

Body Length:

2.250 inches

Body Width:

1.141 inches

Body Height:

1.125 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.600 inches

Vibration Resistance Range In Hertz:

+5.0/+500.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.600 inches

Operating Temperature Range:

-55.0 to 75.0 degrees celsius

Reference Frequency Per Function:

4.6 megahertz blank

Input Impedance Per Function W/load:

8.0 kilohms blank

Output Impedance Per Function W/source Across Input:

350.0 ohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

6.0 blank

Functional Terminal Type And Quantity:

2 tab, solder lug ground 3rd function

Maximum Dielectric Withstanding Ac Rms Voltage:

500.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

4.48 megahertz blank and 4.58 megahertz blank and 4.62 megahertz blank and 4.72 megahertz blank

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

4.58 megahertz blank and 4.62 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 6.0 blank and 6.0 blank and 60.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0