

View Online at https://aerobasegroup.com/nsn/5915-00-031-4165

Overall Length:	
4.344 inches	
Body Length:	
2.500 inches	
Body Outside D	iameter:
1.250 inches	
Vibration Resist	ance Range In Hertz:
+10.0 to 2000.0	
Operating Temp	urature Range:
-65.0 to 85.0 deg	rees celsius
Average Life Ra	ting In Hours:
250.0	
Source Impedar	ce Rating Per Function:
50.0 ohms blank	
Load Impedance	Per Function:
50.0 ohms blank	
Operating Curre	nt Rating Per Function In Amps:
10.0 blank	
Maximum Voltag	ge Drop Per Function:
500.0 millivolts de	blank
Principal Circuit	ry Type Per Function:
Inductance-capad	sitance blank
Mounting Facilit	y Screw Thread Series Designator:
Unef	
Inclosure Type:	
Hermetically seal	ed
Mounting Facilit	y Type And Quantity:
1 threaded bushi	ng
Functional Term	inal Type And Quantity:
1 tab, solder lug	output 2nd function
Operating Voltag	ge Rating And Type Per Function:
100.0 volts dc bla	nk
Thread Size:	
0.625 inches	
Style Designato	r:
Round terminal/te	erminals on opposite surfaces
Test Data Docur	
81349-milf15733	specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
	commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
	d performance requirements and test conditions that are shown as "typical" "average" "", etc.). And 81340-milf1573

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-milf15733/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Shelf Life:

NI/o



Demilitarization:

Yes - demil/mli

Fiig:

A047b0