NSN 5915-00-043-2580

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-043-2580

| Overall Length: |
|---|
| 6.375 inches |
| Overall Height: |
| 1.766 inches |
| Body Length: |
| 3.375 inches |
| Body Width: |
| 0.750 inches |
| Body Height: |
| 1.266 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 3.000 inches |
| Vibration Resistance Range In Hertz: |
| +5.0 to 500.0 |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 0.938 inches |
| Operating Tempurature Range: |
| -55.0 to 125.0 degrees celsius |
| Reference Frequency Per Function: |
| 300.0 megahertz blank |
| Source Impedance Rating Per Function: |
| 50.0 ohms blank |
| Load Impedance Per Function: |
| 50.0 ohms blank |
| Mounting Facility Screw Thread Series Designator: |
| Unc |
| Inclosure Type: |
| Encased |
| Mounting Facility Type And Quantity: |
| 4 threaded hole |
| Insertion Loss At Reference Frequency Per Function In Decibels: |
| 0.3 blank |
| Functional Terminal Type And Quantity: |
| 1 connector, receptacle input 1st function |
| Specified Frequencies Of Discrimination Per Function: |
| 200.00 megahertz blank and 400.00 megahertz blank and 900.00 megahertz blank and 1.30 gigahertz blank |
| Thread Size: |
| 0.112 inches |
| Frequency Band Width Per Function: |
| 200.00 megahertz blank and 400.00 megahertz blank |

1.0 blank and 1.0 blank and 58.0 blank and 58.0 blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

NSN 5915-00-043-2580

Low Pass Filter - Page 2 of 2



| Style | De | sia | nato | ١r٠ |
|-------|-----|------|------|------------|
| OLYIC | De. | oig: | IIau | <i>,</i> , |

Rectangular terminal/terminals on two surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0