NSN 5915-00-043-2580

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-043-2580

Overall Length:
6.375 inches
Overall Height:
1.766 inches
Body Length:
3.375 inches
Body Width:
0.750 inches
Body Height:
1.266 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
3.000 inches
Vibration Resistance Range In Hertz:
+5.0 to 500.0
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.938 inches
Operating Tempurature Range:
-55.0 to 125.0 degrees celsius
Reference Frequency Per Function:
300.0 megahertz blank
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
4 threaded hole
Insertion Loss At Reference Frequency Per Function In Decibels:
0.3 blank
Functional Terminal Type And Quantity:
1 connector, receptacle input 1st function
Specified Frequencies Of Discrimination Per Function:
200.00 megahertz blank and 400.00 megahertz blank and 900.00 megahertz blank and 1.30 gigahertz blank
Thread Size:
0.112 inches
Frequency Band Width Per Function:
200.00 megahertz blank and 400.00 megahertz blank

1.0 blank and 1.0 blank and 58.0 blank and 58.0 blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

NSN 5915-00-043-2580

Low Pass Filter - Page 2 of 2



Style	De	sia	nato	١r٠
OLYIC	De.	oig:	IIau	<i>,</i> ,

Rectangular terminal/terminals on two surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0