## NSN 5915-00-045-5287

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-045-5287

Overall Length:
2.812 inches
Body Length:
2.250 inches
Body Width:
0.359 inches
Body Height:
1.062 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
2.550 inches
Vibration Resistance Range In Hertz:
+5.0 to 500.0
Operating Tempurature Range:
-62.0 to 90.0 degrees celsius
Reference Frequency Per Function:
2.5 kilohertz blank
Source Impedance Rating Per Function:
3.8 kilohms blank
Load Impedance Per Function:
3.8 kilohms blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
2 threaded hole
Insertion Loss At Reference Frequency Per Function In Decibels:
3.0 blank
Functional Terminal Type And Quantity:
1 turret output 2nd function
Specified Frequencies Of Discrimination Per Function:
1.00 kilohertz blank and 4.00 kilohertz blank and 20.00 kilohertz blank and 500.00 kilohertz blank
Thread Size:
0.112 inches
Body Material:
Metal
Frequency Band Width Per Function:
1.00 kilohertz blank and 4.00 kilohertz blank
Discrimination At Specificationified Frequencies Per Function In Decibels:
3.0 blank and 3.0 blank and 50.0 blank and 50.0 blank

100.0 volts at sea level

**Maximum Dielectric Withstanding Dc Voltage:** 

## NSN 5915-00-045-5287

Low Pass Filter - Page 2 of 2

Fiig: A047b0



Style Designator:
Rectangular terminal/terminals on opposite surfaces
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No