

View Online at <https://aerobasegroup.com/nsn/5915-00-049-8484>

**Operating Temperature Range:**

-28.0/+85.0 degrees celsius

**Reference Frequency Per Function:**

4.25 kilohertz blank

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

1 threaded stud

**Features Provided:**

Moisture resistant

**Insertion Loss At Reference Frequency Per Function In Decibels:**

3.0 blank

**Maximum Dielectric Withstanding Ac Rms Voltage:**

500.0 volts at sea level

**Specified Frequencies Of Discrimination Per Function:**

3.50 kilohertz blank and 24.00 kilohertz blank and 4.50 kilohertz blank and 5.00 kilohertz blank

**Thread Size:**

0.138 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

4.00 kilohertz blank and 4.50 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

3.0 blank and 40.0 blank

**Voltage Standing Wave Ratio Frequency Limits Per Function:**

4.0 kilohertz blank and 4.5 kilohertz blank

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A047b0