

View Online at <https://aerobasegroup.com/nsn/5915-00-051-2181>

Overall Height:

1.516 inches

Body Length:

0.750 inches

Body Width:

0.750 inches

Body Height:

1.125 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.562 inches

Vibration Resistance Range In Hertz:

+10.0 to 55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.562 inches

Operating Temperature Range:

-55.0 to 105.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

400.0 hertz blank

Input Impedance Per Function W/load:

10.0 kilohms blank

Output Impedance Per Function W/source Across Input:

10.0 kilohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

6.0 blank

Functional Terminal Type And Quantity:

2 pin ground 3rd function

Maximum Dielectric Withstanding Ac Rms Voltage:

500.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

200.00 hertz blank and 388.00 hertz blank and 412.00 hertz blank and 800.00 hertz blank

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

388.00 hertz blank and 412.00 hertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

35.0 blank and 2.0 blank and 2.0 blank and 35.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0