

View Online at <https://aerobasegroup.com/nsn/5915-00-051-6923>

**Overall Height:**

2.000 inches

**Body Length:**

1.688 inches

**Body Width:**

1.188 inches

**Body Height:**

1.625 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 1.234 inches and 1.266 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 0.734 inches and 0.766 inches

**Operating Temperature Range:**

-55.0 to 85.0 degrees celsius

**Reference Frequency Per Function:**

297.75 hertz blank

**Source Impedance Rating Per Function:**

10.0 kilohms blank

**Load Impedance Per Function:**

10.0 kilohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

4 threaded stud

**Features Provided:**

Moisture resistant

**Insertion Loss At Reference Frequency Per Function In Decibels:**

6.0 blank

**Functional Terminal Type And Quantity:**

1 pin output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

295.50 hertz blank and 300.00 hertz blank and 302.25 hertz blank and 304.50 hertz blank

**Thread Size:**

0.138 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

295.50 hertz blank and 300.00 hertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

26.0 blank and 35.0 blank

**Voltage Standing Wave Ratio Frequency Limits Per Function:**

295.5 hertz blank and 300.0 hertz blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0