

View Online at <https://aerobasegroup.com/nsn/5915-00-051-6923>

Overall Height:

2.000 inches

Body Length:

1.688 inches

Body Width:

1.188 inches

Body Height:

1.625 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 1.234 inches and 1.266 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.734 inches and 0.766 inches

Operating Temperature Range:

-55.0 to 85.0 degrees celsius

Reference Frequency Per Function:

297.75 hertz blank

Source Impedance Rating Per Function:

10.0 kilohms blank

Load Impedance Per Function:

10.0 kilohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded stud

Features Provided:

Moisture resistant

Insertion Loss At Reference Frequency Per Function In Decibels:

6.0 blank

Functional Terminal Type And Quantity:

1 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

295.50 hertz blank and 300.00 hertz blank and 302.25 hertz blank and 304.50 hertz blank

Thread Size:

0.138 inches

Body Material:

Metal

Frequency Band Width Per Function:

295.50 hertz blank and 300.00 hertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

26.0 blank and 35.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

295.5 hertz blank and 300.0 hertz blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0