

View Online at <https://aerobasegroup.com/nsn/5915-00-052-5247>

Overall Height:

1.844 inches

Body Length:

2.500 inches

Body Width:

1.750 inches

Body Height:

1.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.969 inches

Vibration Resistance Range In Hertz:

+5.0 to 33.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.219 inches

Operating Temperature Range:

+0.0 to 50.0 degrees celsius

Average Life Rating In Hours:

2000.0

Reference Frequency Per Function:

200.0 kilohertz blank

Source Impedance Rating Per Function:

8.2 kilohms blank

Load Impedance Per Function:

8.2 kilohms blank

Principal Circuitry Type Per Function:

Crystal blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded stud

Features Provided:

Moisture resistant and shock resistant

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

Functional Terminal Type And Quantity:

1 tab, solder lug input 1st function 1 tab, solder lug output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

100.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

200.10 kilohertz blank and

Thread Size:

0.138 inches

Body Material:

Metal

Frequency Band Width Per Function:

199.95 kilohertz blank and 200.10 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

6.0 blank and 60.0 blank

Body Surface Treatment:

Tin

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0