

View Online at <https://aerobasegroup.com/nsn/5915-00-052-5906>

Overall Height:

4.000 inches

Body Length:

1.750 inches

Body Width:

1.250 inches

Body Height:

3.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.250 inches

Vibration Resistance Range In Hertz:

+10.0 to 55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

Operating Temperature Range:

+0.0 to 105.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

2.375 kilohertz blank

Input Impedance Per Function W/load:

10.0 kilohms blank

Output Impedance Per Function W/source Across Input:

10.0 kilohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

1 threaded stud 1st function

Insertion Loss At Reference Frequency Per Function In Decibels:

1.0 blank

Functional Terminal Type And Quantity:

1 tab, solder lug output 2nd function

Specified Frequencies Of Discrimination Per Function:

34.00 hertz blank and 150.00 hertz blank and 4.80 kilohertz blank and 14.00 kilohertz blank

Thread Size:

0.138 inches

Frequency Band Width Per Function:

150.00 hertz blank and 4.80 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 1.0 blank and 1.0 blank and 40.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0