

View Online at <https://aerobasegroup.com/nsn/5915-00-054-3044>

Overall Length:

Between 1.568 inches and 1.578 inches

Overall Height:

3.330 inches

Body Length:

1.250 inches

Body Height:

3.000 inches

Unthreaded Mounting Hole Diameter:

Between 0.164 inches and 0.169 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.750 inches

Vibration Resistance Range In Hertz:

+10.0 to 500.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

Operating Temperature Range:

-40.0 to 71.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

1.0 kilohertz blank

Input Impedance Per Function W/load:

600.0 ohms blank

Output Impedance Per Function W/source Across Input:

600.0 ohms blank

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 unthreaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

2.5 blank

Functional Terminal Type And Quantity:

2 pin ground 3rd function

Specified Frequencies Of Discrimination Per Function:

300.00 hertz blank and 3.50 kilohertz blank and 4.00 kilohertz blank and 6.00 kilohertz blank

Frequency Band Width Per Function:

300.00 hertz blank and 3.50 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

2.5 blank and 2.5 blank and 25.0 blank and 50.0 blank

Unpackaged Unit Weight:

8.000 ounces

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Test Data Document:

00724-08-00691-000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0