

View Online at <https://aerobasegroup.com/nsn/5915-00-054-5535>

Overall Height:

1.312 inches

Body Length:

1.500 inches

Body Width:

0.750 inches

Body Height:

0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.000 inches

Vibration Resistance Range In Hertz:

+10.0 to 55.0

Operating Temperature Range:

-28.0 to 75.0 degrees celsius

Reference Frequency Per Function:

9.07 megahertz blank

Source Impedance Rating Per Function:

600.0 ohms blank

Load Impedance Per Function:

600.0 ohms blank

Input Impedance Per Function W/load:

600.0 ohms blank

Output Impedance Per Function W/source Across Input:

600.0 ohms blank

Principal Circuitry Type Per Function:

Crystal blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

5.0 blank

Functional Terminal Type And Quantity:

1 pin output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

3.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

9.062 megahertz blank and 9.0696 megahertz blank and 9.0704 megahertz blank and 9.078 megahertz blank

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

9.0696 megahertz blank and 9.0704 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

65.0 blank and 6.0 blank and 6.0 blank and 65.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A047b0