

View Online at https://aerobasegroup.com/nsn/5915-00-057-3349

Overall Length:
3.188 inches
Body Length:
2.000 inches
Body Width:
1.125 inches
Body Height:
1.250 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.375 inches
Operating Tempurature Range:
-55.0/+85.0 degrees celsius
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Operating Current Rating Per Function In Amps:
0.060 blank
Principal Circuitry Type Per Function:
Inductance-capacitance blank
Mounting Facility Screw Thread Series Designator:
Unc
Unc
Unc Inclosure Type:
Unc Inclosure Type: Hermetically sealed
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity:
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded stud
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded stud Functional Terminal Type And Quantity:
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded stud Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded stud Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function:
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded stud Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 600.0 volts dc blank
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded stud Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 600.0 volts dc blank Thread Size:
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded stud Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 600.0 volts dc blank Thread Size: 0.138 inches
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded stud Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 600.0 volts dc blank Thread Size: 0.138 inches Body Material:
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded stud Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 600.0 volts dc blank Thread Size: 0.138 inches Body Material: Metal
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded stud Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 600.0 volts dc blank Thread Size: 0.138 inches Body Material: Metal Maximum Dielectric Withstanding Dc Voltage:
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded stud Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 600.0 volts dc blank Thread Size: 0.138 inches Body Material: Metal Maximum Dielectric Withstanding Dc Voltage: 1.2 kilovolts at sea level
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded stud Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 600.0 volts dc blank Thread Size: 0.138 inches Body Material: Metal Maximum Dielectric Withstanding Dc Voltage: 1.2 kilovolts at sea level Style Designator:
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded stud Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 600.0 volts dc blank Thread Size: 0.138 inches Body Material: Metal Maximum Dielectric Withstanding Dc Voltage: 1.2 kilovolts at sea level Style Designator: Rectangular terminal/terminals on opposite surfaces

Radio Frequency Interference Filter - Page 2 of 2



Demilitarization:

No

Fiig:

A047b0